Commom Mode Choke

AWCU Series ISO9001 | ISO14001 | IATF16949

Pulse
a YAGEO company

REACH Compliant





Noise Suppression | Unshield | Wire Wound | Ferrite | General Signal line


Part Numbering

A	WCU	00	201212	300	M	02
Grade	Series Name	Control Code	Dimensions Code (mm)	Impedance (Ω)	Tolerance	Internal Code
			2.05x1.25x1.2	300 30	M ±20%	02 USB2.0
			3.2x1.6x1.9	121 120	Y ±25%	03 USB3.0


A	WCU	00	453226	510	X	G0
Grade	Series Name	Control Code	Dimensions Code (mm)	Inductance (uH)	Tolerance	Internal Code
			3.3x2.5x2.3	110 11	T ±30%	G0
			3.3x2.5x2.5	510 51	X -	TE
			4.5x3.2x2.6	101 100		T2
			4.5x3.2x2.8			MF

AWCU00201212-02 Type

Dimensions / Recommended Land Pattern



NO Polarity Equivalent circuit



unit:mm

Electrical Characteristics


Part No.	Impedance (Ω)	Test Freq. (MHz)	RDC (Ω)Max.	IDC (mA)	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.	Tolerance (±%)
AWCU00201212300□02	30	100	0.2	450	50	125	10	20
AWCU00201212670□02	67	100	0.25	400	50	125	10	20
AWCU00201212750□02	75	100	0.3	360	50	125	10	20
AWCU00201212900□02	90	100	0.35	330	50	125	10	20
AWCU00201212121□02	120	100	0.3	400	50	125	10	20
AWCU00201212161□02	160	100	0.35	350	50	125	10	20
AWCU00201212181□02	180	100	0.35	330	50	125	10	20
AWCU00201212201□02	200	100	0.35	330	50	125	10	20
AWCU00201212221□02	220	100	0.35	310	50	125	10	20
AWCU00201212261□02	260	100	0.4	300	50	125	10	20
AWCU00201212301□02	300	100	0.4	290	50	125	10	20
AWCU00201212361□02	360	100	0.45	280	50	125	10	20
AWCU00201212371□02	370	100	0.45	280	50	125	10	20
AWCU00201212501□02	500	100	0.55	170	50	125	10	20
AWCU00201212671□02	670	100	0.6	140	50	125	10	20
AWCU00201212901□02	900	100	0.6	80	50	125	10	20

Note: When ordering, please specify tolerance code. Tolerance: M=±20%

1. Operating temperature range - 50℃ ~ 150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. IDC for Inductance drop 10% from its value without current.
4. Measure Equipment:
   Z: Agilent HP4287A+Agilent 16197A
   RDC: Chroma 16502 (Single Wire Test Value)
   IDC: HP4284A+HP42841A/HP4285A+HP42841A


AWCU00201212-02 Type

Characteristics Graph




AWCU00321619-02 Type

Dimensions / Recommended Land Pattern



NO Polarity Equivalent circuit



unit:mm

Electrical Characteristics


Part No.	Impedance (Ω)	Test Freq. (MHz)	RDC (Ω)Max.	IDC (mA)	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.	Tolerance (±%)
AWCU00321619900□02	90	100	0.3	370	50	125	10	20
AWCU00321619121□02	120	100	0.3	370	50	125	10	20
AWCU00321619161□02	160	100	0.4	340	50	125	10	20
AWCU00321619221□02	220	100	0.4	320	50	125	10	20
AWCU00321619261□02	260	100	0.5	310	50	125	10	20
AWCU00321619601□02	600	100	0.8	260	50	125	10	20
AWCU00321619102□02	1000	100	1	230	50	125	10	20
AWCU00321619222□02	2200	100	1.2	200	50	125	10	20

Note: When ordering, please specify tolerance code. Tolerance: M=±20%

1. Operating temperature range - 50℃ ~ 150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. IDC for Inductance drop 10% from its value without current.
4. Measure Equipment:
   Z: Agilent HP4287A+Agilent 16197A
   RDC: Chroma 16502 (Single Wire Test Value)
   IDC: HP4284A+HP42841A/HP4285A+HP42841A


AWCU00321619-02 Type

Characteristics Graph




AWCU00332523 Type

Dimensions / Recommended Land Pattern



NO Polarity Equivalent circuit



unit:mm

Electrical Characteristics

Part No.	Impedance (Ω)10MHz Min.(Typ.)	Inductance (uH)+50/-30	Stary Inductance (uH)Typ.	Test Freq.	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)Max.	Insulation Resistance (MΩ)Min.
AWCU00332523110XT2	300(550)	11	0.05	100kHz	0.4	300	80	10
AWCU00332523220XT2	500(1100)	22	0.06	100kHz	0.5	250	80	10
AWCU00332523510XT2	1000(2600)	51	0.09	100kHz	0.7	200	80	10
AWCU00332523101XT2	2200(5100)	100	0.13	100kHz	1.5	150	80	10

Note:

1. Operating temperature range - 50℃ ~ 150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 15℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B

Electrical Characteristics


Part No.	Inductance (uH)+50/-30	Test Freq.	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.
AWCU00332523101XMF	100	100kHz	2.2	115	50	125	10


Note:

1. Operating temperature range - 40℃ ~ 125℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 15℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B

AWCU00332523 Type


■ Characteristics Graph






AWCU00332525 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics


Part No.	Impedance (Ω)10MHz Min.(Typ.)	Inductance (uH)+50/-30	Stary Inductance (uH)Typ.	Test Freq.	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)Max.	Insulation Resistance (MΩ)Min.
AWCU00332525110XG0	300(550)	11	0.05	100kHz	0.4	300	80	10
AWCU00332525220XG0	500(1100)	22	0.06	100kHz	0.5	250	80	10
AWCU00332525510XG0	1000(2600)	51	0.09	100kHz	0.7	200	80	10
AWCU00332525101XG0	2200(5100)	100	0.13	100kHz	1.5	150	80	10

Note:

1. Operating temperature range - 50℃ ~ 150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 15℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B


AWCU00332525 Type

■ Characteristics Graph




AWCU00453226-T2 Type

■ Dimensions/Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics


Part No.	Inductance (uH)	Test Freq.	Impedance (Ω) Min.	Impedance (Ω) Typ.	Test Freq. (MHz)	RDC (Ω) Max.	Irms (mA) Max.	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.	Tol. (±%)
AWCU00453226113□T2	11	100kHz	300	600	10	0.6	250	50	125	10	30
AWCU00453226223□T2	22	100kHz	500	1200	10	1	200	50	125	10	30
AWCU00453226513□T2	51	100kHz	1000	2800	10	1	200	50	125	10	30
AWCU00453226104□T2	100	100kHz	2000	5800	10	2	150	50	125	10	30

Note: When ordering, please specify tolerance code. Tolerance: T=±30%

1. Operating temperature range - 50℃ ~ 150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 40℃ rise above 25℃ ambient.
4. Measure Equipment:
   Z: HP4286A / HP4287A / AgilentE4991A
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B


AWCU00453226-T2 Type

■ Characteristics Graph




AWCU00453226-M2 Type

■ Dimensions/Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics


Part No.	Inductance (uH)	Test Freq.	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.	Tolerance (±%)
AWCU00453226113□M2	11	100kHz,100mV	0.5	360	50	125	10	30
AWCU00453226223□M2	22	100kHz,100mV	0.6	310	50	125	10	30
AWCU00453226513□M2	51	1MHz,200mV	1	230	50	125	10	30
AWCU00453226104□M2	100	1MHz,200mV	2	200	50	125	10	30

Note: When ordering, please specify tolerance code. Tolerance: T=±30%

1. Operating temperature range - 50℃ ~ 150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 40℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B


AWCU00453226-M2 Type

Characteristics Graph




AWCU00453226-G0 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm


■ Electrical Characteristics

Part No.	Inductance1 (uH) 100kHz(50/-30%)	Inductance2 (uH) 1MHz(Typ.)	Impedance (Ω) 10MHz(Typ.)	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.
AWCU00453226110XG0	11	-	670	0.5	360	50	125	10
AWCU00453226220XG0	22	-	1450	0.6	310	50	125	10
AWCU00453226510XG0	51	51	3500	1	230	50	125	10
AWCU00453226101XG0	100	100	6500	2	200	50	125	10

1. Operating temperature range - 50℃ ~ 150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 40℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B


AWCU00453226-G0 Type

■ Characteristics Graph




AWCU00453228 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics


Part No.	Inductance (uH)+60/-20	Test Freq.	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)Max.	Insulation Resistance (MΩ)Min.
AWCU00453228201XTE	200	100kHz	4.5	100	50	10

Note:

1. Operating temperature range - 40℃ ~ 125℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 15℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B


AWCU00453228 Type

Characteristics Graph




AWCU00201212-03 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics


Part No.	Impedance (Ω)	Test Freq. (MHz)	RDC (Ω)Max.	IDC (mA)	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.	Tolerance (±%)
AWCU00201212500□03	50	100	0.2	500	50	125	10	25
AWCU00201212670□03	67	100	0.3	500	50	125	10	25
AWCU00201212900□03	90	100	0.3	500	50	125	10	25
AWCU00201212121□03	120	100	0.35	330	50	125	10	25

Note: When ordering, please specify tolerance code. Tolerance: Y=±25%

1. Operating temperature range - 50℃ ~ 150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. IDC for Inductance drop 10% from its value without current.
4. Measure Equipment:
   Z: Agilent HP4287A+Agilent 16197A
   RDC: Chroma 16502 (Single Wire Test Value)
   IDC: HP4284A+HP42841A/HP4285A+HP42841A


AWCU00201212-03 Type

■ Characteristics Graph




AWCU00201212500Y03


Insertion Loss For HDMI2.0 Testing:



Insertion Loss For USB3.0 Testing:




TDR For HDMI2.0 Testing:




Parameter Name: HDMI2.0 Choke Impedance c1	
Spc Max: 115 Ω	Spc Min: 85 Ω
Max:100.73 Ohms at 0.7552 ns	Min:91.30 Ohms at 0.4827 ns
ΔΩ: 9.43	Avg: 96.02 Ohms
	Result: Pass

TDR For USB3.0 Testing:




Parameter Name: Choke Impedance C1	
Spc Max: 105 Ω	Spc Min: 75 Ω
Max:100.25 Ohms at 0.6200 ns	Min:86.88 Ohms at 0.4825 ns
ΔΩ: 13.36	Avg: 93.57 Ohms
	Result: Pass

Eye DiagramFor HDMI2.0 Testing:



Parameter Name: HDMI2.0 Choke Eye Diagram with 25ps c1	
Display Mode: Not a standard mode	
dRate: 6 Gbits/s; 166.7 ps	V: 500 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass


Eye DiagramFor USB3.0 Testing:




Parameter Name: USB3.0 Choke Eye Diagram C1	
Display Mode: Not a standard mode	
dRate: 5 Gbits/s; 200.0 ps	V: 250 mV;Gain: 0 dB;Off: 0 mV

AWCU00201212670Y03


Insertion Loss For HDMI2.0 Testing:



Insertion Loss For USB3.0 Testing:




TDR For HDMI2.0 Testing:




Parameter Name: HDMI2.0 Choke Impedance c1	
Spc Max: 115 Ω	Spc Min: 85 Ω
Max:100.99 Ohms at 0.6645 ns	Min:90.10 Ohms at 0.4614 ns
ΔΩ: 10.89	Avg: 95.54 Ohms
	Result: Pass

TDR For USB3.0 Testing:




Parameter Name: Choke Impedance C1	
Spc Max: 105 Ω	Spc Min: 75 Ω
Max:101.51 Ohms at 0.6150 ns	Min:82.65 Ohms at 0.4775 ns
ΔΩ: 18.86	Avg: 92.08 Ohms
	Result: Pass

Eye DiagramFor HDMI2.0 Testing:



Parameter Name: HDMI2.0 Choke Eye Diagram with 25ps c1	
Display Mode: Not a standard mode	
dRate: 6 Gbits/s; 166.7 ps	V: 500 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass


Eye DiagramFor USB3.0 Testing:




Parameter Name: USB3.0 Choke Eye Diagram C1	
Display Mode: Not a standard mode	
dRate: 5 Gbits/s; 200.0 ps	V: 250 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass

AWCU00201212900Y03


Insertion Loss For HDMI2.0 Testing:



Insertion Loss For USB3.0 Testing:




TDR For HDMI2.0 Testing:




Parameter Name: HDMI2.0 Choke Impedance c1	
Spc Max: 115 Ω	Spc Min: 85 Ω
Max:100.15 Ohms at 0.7552 ns	Min:85.35 Ohms at 0.5202 ns
ΔΩ: 14.80	Avg: 92.75 Ohms
	Result: Pass

TDR For USB3.0 Testing:




Parameter Name: Choke Impedance C1	
Spc Max: 105 Ω	Spc Min: 75 Ω
Max:98.68 Ohms at 0.3738 ns	Min:79.36 Ohms at 0.5238 ns
ΔΩ: 19.33	Avg: 89.02 Ohms
	Result: Pass

Eye DiagramFor HDMI2.0 Testing:



Parameter Name: HDMI2.0 Choke Eye Diagram with 25ps c1	
Display Mode: Not a standard mode	
dRate: 6 Gbits/s; 166.7 ps	V: 500 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass


Eye DiagramFor USB3.0 Testing:




Parameter Name: USB3.0 Choke Eye Diagram C1	
Display Mode: Not a standard mode	
dRate: 5 Gbits/s; 200.0 ps	V: 250 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass

AWCU00201212121Y03


Insertion Loss For HDMI2.0 Testing:



Insertion Loss For USB3.0 Testing:




TDR For HDMI2.0 Testing:




Parameter Name: HDMI2.0 Choke Impedance c1	
Spc Max: 115 Ω	Spc Min: 85 Ω
Max:101.21 Ohms at 0.7077 ns	Min:91.02 Ohms at 0.4927 ns
ΔΩ: 10.19	Avg: 96.12 Ohms
	Result: Pass

TDR For USB3.0 Testing:




Parameter Name: Choke Impedance C1	
Spc Max: 105 Ω	Spc Min: 75 Ω
Max:100.24 Ohms at 0.6263 ns	Min:85.90 Ohms at 0.5275 ns
ΔΩ: 14.35	Avg: 93.07 Ohms
	Result: Pass

Eye DiagramFor HDMI2.0 Testing:



Parameter Name: HDMI2.0 Choke Eye Diagram with 25ps c1	
Display Mode: Not a standard mode	
dRate: 6 Gbits/s; 166.7 ps	V: 500 mV;Gain: 0 dB;Off: 0 mV


Eye DiagramFor USB3.0 Testing:



Parameter Name: USB3.0 Choke Eye Diagram C1	
Display Mode: Not a standard mode	
dRate: 5 Gbits/s; 200.0 ps	V: 250 mV;Gain: 0 dB;Off: 0 mV

Packaging

Tape Dimensions



Reel Dimensions

Figure1





Figure 2



Dimensions in mm

TYPE	Tape Dimensions										Reel Dimensions					Quantity
	A0	B0	K0	D	E	F	W	P	P0	P2	Fig.	A	B	C	D	PCS/REEL
AWCU00201212	1.5	2.25	1.45	1.5	1.75	3.5	8	4	2	2	1	178	60	12	1.5	2000
AWCU00321619	1.76	3.47	2.05	1.5	1.75	3.5	8	4	2	2	1	178	60	12	1.5	2000
AWCU00332523	2.72	3.52	2.45	1.5	1.75	5.5	12	4	4	2	1	178	60	12	1.5	1500
AWCU00332525	2.72	3.52	2.60	1.5	1.75	5.5	12	4	4	2	1	178	60	12	1.5	1500
AWCU00453226	3.6	4.9	3	1.5	1.75	5.5	12	8	4	2	2	330	100	13	13.4	2500
AWCU00453228	3.6	4.9	3	1.5	1.75	5.5	12	8	4	2	2	330	100	13	13.4	2500

For More Information:
Americas - prodinfo_power_americas@yageo.com | **Europe -** prodinfo_power_emea@yageo.com | **Asia -** prodinfo_power_asia@yageo.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2022. Pulse Electronics, Inc. All rights reserved.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Pulse Electronics:

PAT6261.003NLT PG2290.151HLT PGL6395.121HLT JXD2-0Z10NL PA4343.451NLT PD617-6000M243 AWCS0012070736NJ00 PA4320.334NLT ANT1204F007R0870A JXD0-2015NL PA4320.104NLT W3078 BBUP00201209121Y00 DPX1608LKF3R2460A PD380-4000S1NF PA4341.221NLT W1093 BDHE002520122R2MQ1 BSPQ000603041N4B00 E5J88-032-02-L PA0369NL PA4343.361NLT PE-68386NLT W1902 W3334B0150 BSPQ000603043N0B00 PA2744NL PA4341.301NLT PE-67100NL P0585NL