Clevis foot
CRLNG-40

Part number: 161841



General operating condition

Data sheet

Feature	Value
Size	40
Based on norm	ISO 15552 (previously also VDMA 24562, ISO 6431, NF E49 003.1, UNI 10290)
Mounting position	Any
Corrosion resistance class (CRC)	4 - Particularly high corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Metals with more than 1% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils
Ambient temperature	-40 °C ... 80 °C
Product weight	161 g
Note on materials	RoHS-compliant
Mounting material	Electropolished High-alloy steel
Material of bearing	Polymer

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

153151 HGL-1/8-QS-6 NPQP-L-Q10-E-FD-P10 NPQP-Y-Q6-E-FD-P10 QSML-6 QSS-8-F 153307 QSY-6H-4 VBQF-U-G14-E 153031 CRVZS-0.4 DSBC-80-20-D3-PPSA-N3 NPQP-D-Q4-S8-FD-P10 NPQP-T-Q8-E-FD-P10 NPQP-Y-R12-Q12-FD QSF-1/4-8-B VABM-B10-25S-G38-10 153269 153367 QS-10H-6 QSLL-G1/2-12 SGS-M10X1,25 QS-1/2-16 QS-1/8-8-I QSF-3/8-8-B VABM-B10-25S-G38-6-P3 NPQH-T-Q14-E-P10 NPQP-LQ-R18-Q4-FD-P10 NPQP-LQ-R18-Q8-FD-P10 SASC-P4-A-M8-A