FEED THROUGH DOUBLE LEVEL

	ODL2.5	ODL2.5(I.S)	ODLG2.5	ODLG2.5(I.S)
				
				
Dimensions & Weight	Double Level with Offset	Double Level with Offset Internally Shorted Upper / Lower Level	Double Level with Offset Ground Connection	Double Level with Offset Internally Shorted / Ground Connection
Width	**5 mm**	**5 mm**	**5 mm**	**5 mm**
Length	62.0 mm	62.0 mm	62.0 mm	62.0 mm
Height w DIN Rail 35 x 7.5 mm 35 x 15 mm	63.0 mm 70.5 mm	63.0 mm 70.5 mm	63.0 mm 70.5 mm	63.0 mm 70.5 mm
Weight per piece	13.0 g	14.2 g	15.3 g	17.0 g
Technical Data/Ratings				
Approvals	cULus E220514 / CSA / IEC 60947-7-1	cULus E220514 / CSA / IEC 60947-7-1	cULus E220514 / CSA / IEC 60947-7-1	cULus E220514 / CSA / IEC 60947-7-1
Wire Size (solid / stranded)	**24-12 AWG** / 0.2-2.5 mm²	**24-12 AWG** / 0.2-2.5 mm²	**24-12 AWG** / 0.2-2.5 mm²	**24-12 AWG** / 0.2-2.5 mm²
Voltage Rating	300 V / 800 V AC/DC	300 V / 800 V AC/DC	300 V / 800 V AC/DC	300 V / 800 V AC/DC
Current Rating	25 A / 24 A	25 A / 24 A	25 A / 24 A	– / –
Torque	4.5 lb-in / 0.4 Nm	4.5 lb-in / 0.4 Nm	4.5 lb-in / 0.4 Nm	4.5 lb-in / 0.4 Nm
Insulation Material	Polyamide 66	Polyamide 66	Polyamide 66	Polyamide 66
Installation Instructions				
Wire Stripping Length	8 mm	8 mm	8 mm	8 mm
Screwdriver	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm
Terminal Blocks	Cat. No. / Std. Pk.	Cat. No. / Std. Pk.	Cat. No. / Std. Pk.	Cat. No. / Std. Pk.
Grey	**ODL2.5** 50	**ODL2.5(I.S)** 50	**ODLG2.5** 50	**ODLG2.5(I.S)** 50
Stackable Clip-on	ODL2.5A 50	ODL2.5A(I.S) 50	ODLG2.5A 50	ODLG2.5A(I.S) 50
Red R	ODL2.5/R 50	ODL2.5/R 50	– –	– –
Blue BU	ODL2.5/BU 50	ODL2.5/BU 50	– –	– –
Black BL	ODL2.5/BL 50	ODL2.5/BL 50	– –	– –
Orange O	ODL2.5/O 50	ODL2.5/O 50	– –	– –
Green G	ODL2.5/G 50	ODL2.5/G 50	– –	– –
Yellow Y	ODL2.5/Y 50	ODL2.5/Y 50	– –	– –
White W	ODL2.5/W 50	ODL2.5/W 50	– –	– –
Accessories	Cat. No. / Std. Pk.	Cat. No. / Std. Pk.	Cat. No. / Std. Pk.	Cat. No. / Std. Pk.
End Plate — Front Side	EPODL2.5 50	EPODL2.5 50	EPODL2.5 50	EPODL2.5 50
End Plate — Back Side	EP1ODL2.5 50	EP1ODL2.5 50	EP1ODL2.5 50	EP1ODL2.5 50
DIN Rail 35mm	2511120 20	2511120 20	2511120 20	2511120 20
DIN Rail 35mm	CA701-15/S 20	CA701-15/S 20	CA701-15/S 20	CA701-15/S 20
End Stop	CA702 50	CA702 50	CA702 50	CA702 50
	CA802 50	CA802 50	CA802 50	CA802 50
	CA202 25	CA202 25	CA202 25	CA202 25
Shorting Link/ Jumpers 2 pole	JX2.5/2 100	JX2.5/2 100	JX2.5/2 100	JX2.5/2 100
3 pole	JX2.5/3 50	JX2.5/3 50	JX2.5/3 50	JX2.5/3 50
4 pole	JX2.5/4 50	JX2.5/4 50	JX2.5/4 50	JX2.5/4 50
5 pole	JX2.5/5 50	JX2.5/5 50	JX2.5/5 50	JX2.5/5 50
6 pole	JX2.5/6 10	JX2.5/6 10	JX2.5/6 10	JX2.5/6 10
7 pole	JX2.5/7 10	JX2.5/7 10	JX2.5/7 10	JX2.5/7 10
8 pole	JX2.5/8 10	JX2.5/8 10	JX2.5/8 10	JX2.5/8 10
10 pole	JX2.5/10 10	JX2.5/10 10	JX2.5/10 10	JX2.5/10 10
Marking Tag	MT5 1 Pk. (100 tags)	MT5 1 Pk. (100 tags)	MT5 1 Pk. (100 tags)	MT5 1 Pk. (100 tags)

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Altech:

5308 903 MVE-153 MVE-253 2623.0 2ALP4LB-048 MVE-152 PS-C12048 5308 901 LK11 Y/R U OKA/KU LK10 Y/R SWL4 3C10UL 4264120 CP1.5 KU340N 1C10UR 2ATL5LB F3P4-IO-110 MC-65A-AC120V-L 5308 921 7211 486 MC-65A-AC230V-L MVS-154-5,08 PSW-48024 2PLB3LB-110 5308902 7211 495 2ALF3LB-110 2P16UL3/6 7211 497 2AB3-NB