
Sub-base-SET MS6-AGD

Part number: 526082



General operating condition

Data sheet

Feature	Value
Size	6
Series	MS
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Temperature of medium	-10 °C ... 60 °C
Product weight	300 g
Pneumatic connection 1	G1/2
Pneumatic connection 2	G1/2
Note on materials	RoHS-compliant
Material of sub-base	Die-cast aluminum
Seals material	NBR

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

153151 153307 NPQP-T-Q8-E-FD-P10 HGL-1/8-QS-6 NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q8-FD-P10 VBQF-U-G14-E NPQP-Y-Q6-E-FD-P10 QS-1/2-16 QSS-8-F QSLL-G1/2-12 SASC-P4-A-M8-A SGS-M10X1,25 DSBC-80-20-D3-PPSA-N3 NPQP-Y-R12-Q12-FD QS-10H-6 QSF-1/4-8-B QSF-3/8-8-B 153031 NPQP-LQ-R18-Q4-FD-P10 QS-1/8-8-I QSY-6H-4 VABM-B10-25S-G38-6-P3 153269 153367 CRVZS-0.4 QSML-6 NPQH-T-Q14-E-P10 NPQP-D-Q4-S8-FD-P10 VABM-B10-25S-G38-10