

Parallel gripper
HGPL-14-40-A-B

Part number: 3361480

FESTO





General operating condition

Data sheet

Feature	Value
Size	14
Stroke per gripper jaw	40 mm
Max. interchangeability	‹0.2 mm
Max. gripper jaw angular play ax, ay	‹0.2 deg
Max. gripper jaw backlash Sz	‹0.05 mm
Rotational symmetry	≤0.2 mm
Pneumatic gripper repetition accuracy	‹0.03 mm
Number of gripper jaws	2
Actuator system	Pneumatic
Mounting position	Any
Mode of operation	Double-acting
Gripper function	Parallel
Gripping force backup	Without
Structural design	Twin piston Guide Piston gate valve T-shape Gear rack/pinion
Position sensing	For proximity sensor
Symbol	00991894
Operating pressure	3 bar ... 8 bar
Max. operating frequency of pneumatic gripper	‹1 Hz
Min. opening time at 6 bar	171 ms
Min. closing time at 6 bar	163 ms
Max. mass per external gripper finger	80 g
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	5 °C ... 60 °C
Gripping force per gripper jaw at 6 bar, opening	126 N
Gripping force per gripper jaw at 6 bar, closing	158 N
Gripping force per gripper jaw at 6 bar, opening	63 N
Gripping force per gripper jaw at 6 bar, closing	79 N
Mass moment of inertia	6.69 kgcm²
Maximum force on gripper jaw Fz, static	500 N
Maximum torque on gripper jaw, Mx static	35 Nm

Feature	Value
Maximum torque on gripper jaw, My static	35 Nm
Maximum torque on gripper jaw, Mz static	35 Nm
Relubrication interval for guidance elements	5 MioCyc
Product weight	440 g
Type of mounting	With internal thread and centering sleeve Via through-hole and centering sleeve
Pneumatic connection	M5
Note on materials	RoHS-compliant
Housing material	Wrought aluminum alloy, smooth-anodized
Gripper jaw material	Hardened steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

NPQP-D-Q4-S8-FD-P10 153151 NPQP-LQ-R18-Q8-FD-P10 QS-10H-6 SASC-P4-A-M8-A VABM-B10-25S-G38-10 153031 NPQP-T-Q8-E-FD-P10 NPQP-Y-Q6-E-FD-P10 QS-1/2-16 QSML-6 CRVZS-0.4 NPQP-L-Q10-E-FD-P10 QSLL-G1/2-12 HGL-1/8-QS-6 NPQH-T-Q14-E-P10 QS-1/8-8-I QSS-8-F QSY-6H-4 SGS-M10X1,25 VBQF-U-G14-E 153307 153367 NPQP-LQ-R18-Q4-FD-P10 QSF-1/4-8-B 153269 DSBC-80-20-D3-PPSA-N3 NPQP-Y-R12-Q12-FD QSF-3/8-8-B VABM-B10-25S-G38-6-P3