技术参数 / Technical parameter




MU-105-ACY
W6.60xD7.20xH2.40

PIN数(Number of contacts) ： 5PIN	插座类型(Socket type) ： MICRO USB
插座类别(Socket category)：母座/Mother seat	操作方式(Operation mode)：卧式/Horizontal
温度范围(Operating temp)：-20°C TO +70°C	操作寿命(Operation life)：5,000 Cycles Min
额定负荷(Rated load)：DC 30V 1.5A	焊接方式(Welding mode)：贴片式/SMT
接触电阻(Contact resistance)：≤50mΩ	包装方式(Packaging method)：卷带/Tape&Reel(TR)
绝缘电阻(Insulation resistance)：≥1000MΩ	最小包装(Minimum packing)：1,500/PCS


外形尺寸(UNIT:MM) / Size Chart

www.xunpudianzi.com

更多资料请参考技术选型档!



线路板安装(UNIT:MM) / Mounting Dimensions



P.C.B LAYOUT(copper-side view)

引脚定义/Pin Definition

PIN	Signal Name	Describe
1	VBUS	+5V
2	D-	Neagative Data Channel
3	D+	Positive Data Channel
4	ID	OTG
5	GND	Ground


XUNPU ELECTRONIC TECHNOLOGY Co., LTD
WWW.XUNPUDIANZI.COM

焊接条件 / Welding conditions

回流焊/Reflow soldering

适用表面贴装型产品/Applicable to surface mount products

温度分布/Temperature distribution



手焊式/Hand welding

项目/Project	条件/condition
焊接温度 Welding temperature	350°C max.
持续焊接时间 Continuous welding time	3s max.
焊剂斗容量 Flux bucket capacity	60W max.

浸焊式/Immersion soldering

项目/Project	条件/condition
助焊剂附着量 Flux adhesion	不附着于零部件贴装面的程度 Not attached to the mounting surface of components
预热温度 Preheating temperature	印刷电路板焊接面的周围温度 100°C max. The temperature around the welding surface of PCB is 100 °C max
预热温度时间 Preheat temperature time	60s max.
焊接温度 welding temperature	260°C max.
焊接浸渍时间 Welding immersion time	5s max.
焊接次数 Welding times	2 times max.

注:

1. 加热方式:以远红外线上下加热方式。
2. 温度测量:用Φ0.1~0.2 的 CA(K)或 CC(T)测量位置在焊接连接部(锡/铜箔面)。
3. 固定方式:采用耐热胶带。

XUNPU ELECTRONIC TECHNOLOGY Co., LTD

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

XUNPU:

FPC-0.5FX-4PWCR-H20 FPC-0.5HF-10PWBR-H20 RJ45-005-014-11 WAFER-XH2.54-4PWZ-H62
FPC-0.5AS-5PWCR-H20 FPC-0.5FX-16PWCR-H20 FPC-1.0AX-4PWCR-H25 DC-031A-A100
MU-103-ARW64 WAFER-PH2.0-3PWB WAFER-WBM4.2-16PJK-GB FPC-0.5AL-6PB
FPC-0.5AX-30PWCR-H20 FPC-1.0HF-4PWAR-H20 SMA-KWE-323C-H13X23-LW FPC-0.5FX-14PWCR-H20
PHB2.0-02-20PZZ WAFER-PH2.0-8PLB WAFER-PH2.0-6PWB WAFER-VH3.96-4PLB
FPC-0.5AX-24PWCR-H20 FPC-0.5FX-4PWBH15 FPC-1.0AX-14PWCR-H25 HDMI-212L
TYPEC-304YDSW-ACP16 WAFER-GH1.25-6PLB FPC-0.5FX-20PWBH15 WAFER-MX1.25B-8PWB
WAFER-PH2.0-11PZZ WAFER-PH2.0-2PJK