Push-in X connector
QSMX-4

Part number: 153379



General operating condition

Data sheet

Feature	Value
Size	Mini
Nominal width	2.5 mm
Mounting position	Any
Design	X-shape
Pack size	10
Structural design	Push-pull principle
Operating pressure for entire temperature range	-0.095 MPa ... 0.6 MPa
Operating pressure for entire temperature range	-0.95 bar ... 6 bar
Operating pressure for entire temperature range	-13.775 psi ... 87 psi
Temperature-dependent operating pressure	-0.095 MPa ... 1.4 MPa
Temperature-dependent operating pressure	-0.95 bar ... 14 bar
Temperature-dependent operating pressure	-13.775 psi ... 203 psi
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-10 °C ... 80 °C
Product weight	4 g
No. of outlets	3
No. of supply lines	1
Pneumatic connection 1	for pneumatic tubing outside diameter 4 mm
Pneumatic connection 2	for pneumatic tubing outside diameter 4 mm
Releasing ring color	Blue
Note on materials	RoHS-compliant
Housing material	PBT
Releasing ring material	POM
Material of tubing seal	NBR
Material of tube retaining claw	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

153367 HGL-1/8-QS-6 QSF-3/8-8-B SGS-M10X1,25 VABM-B10-25S-G38-10 NPQP-D-Q4-S8-FD-P10 QSLL-G1/2-12 QSS-8-F QSY-6H-4 153269 DSBC-80-20-D3-PPSA-N3 NPQP-LQ-R18-Q4-FD-P10 QS-10H-6 QSML-6 SASC-P4-A-M8-A NPQP-Y-Q6-E-FD-P10 VABM-B10-25S-G38-6-P3 153307 NPQP-Y-R12-Q12-FD QS-1/8-8-I VBQF-U-G14-E 153031 153151 NPQP-L-Q10-E-FD-P10 NPQP-T-Q8-E-FD-P10 QS-1/2-16 CRVZS-0.4 NPQH-T-Q14-E-P10 NPQP-LQ-R18-Q8-FD-P10 QSF-1/4-8-B