

Schottky Barrier Rectifiers

Parameter	Value	Unit
V_{RRM}	100	V
$I_{F(AV)}$	10(2*5)	A





TO-252/CS



TO-220F/FCT

Features

- Common cathode structure
- Low power consumption, high efficiency
- Good high-temperature characteristics
- Over voltage protection loop, high reliability

Applications

- Power Factor Correction(PFC)
- Switched Mode Power Supply(SMPS)
- Uninterruptible Power Supply(UPS)
- Air Conditioner

Absolute Maximum Ratings(Ta=25℃,unless otherwise noted)

Parameter		Symbol	Value	Unit
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	100	V
Working Peak Reverse Voltage		V_{RWM}	100	V
Maximum DC Blocking Voltage		V_{DC}	100	V
RMS Reverse Voltage		$V_{R(RMS)}$	70	V
Average Forward Rectified Current	Per Leg	$I_{F(AV)}$	5	A
	Total		10	
Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)		I_{FSM}	200	A
Maximum Junction Temperature		T_J	175	℃
Storage Temperature Range		T_{STG}	-55 to +150	℃

Note:

1.Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

Thermal Data

Parameter		Symbol	Value	Unit
Thermal Resistance from Junction to Ambient	TO-220F	$R_{\theta JA}$	60	℃/W
	TO-252		110	℃/W
Thermal Resistance From Junction To Case	TO-220F	$R_{\theta JC}$	4	℃/W
	TO-252		6	℃/W

Electrical Characteristics (Ta=25℃, unless otherwise specified)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Reverse voltage	$V_{(BR)}$	I_R=0.1mA		100			V
Reverse current	I_R	V_R= 100V			1	100	uA
Forward voltage	V_{F1}	I_F=5A	T_j=25℃		0.78	0.85	V
	V_{F2}	I_F= 10A	T_j=25℃			0.95	V

Notes:
1. Short duration pulse test used to minimize self-heating effect.
2. Thermal resistance junction to case mounted on heatsink.

Typical Characteristics

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: TYPICAL FORWARD CHARACTERISTICS




FIG.3: TOTAL CAPACITANCE DERATING CURVE






FIG.4: TYPICAL REVERSE CHARACTERISTICS




Package Outline Dimensions

TO-252



TO-220F



Symbol	Dimensions In Millimeters	
	Min	Max
A	4.300	4.750
A1	0.7 REF	
A2	2.300	2.850
A3	2.500	2.900
b	0.380	0.420
b1	1.220	1.280
C	1.08	1.200
c	0.480	0.520
D	10.15	10.450
E	15.700	15.950
e	2.574 TYP	
F	3.470 REF	
y	3.200 REF	
h	0.000	0.800
L	28.780	28.900
L1	2.990	3.100

***Important Usage Information and Disclaimer**

The specifications of Zhuhai Hypersemi Co., Ltd. products are not guarantees of product characteristics. They reflect typical performance expected in standard applications, which may vary with specific uses. Users must conduct prior testing for their applications and make necessary adjustments.

Users are responsible for the safety of applications utilizing our products and must implement adequate safety measures to prevent physical injury, fire, or other risks in case of product failure. It is the user's duty to ensure that application designs comply with all applicable laws and standards. Our products must not be used in any applications where a product failure could reasonably result in personal injury, unless specifically authorized in a signed document by Zhuhai Hypersemi Co., Ltd.

No representations or warranties are made regarding the accuracy or completeness of this information, including any claims of non-infringement of third-party intellectual property rights. Zhuhai Hypersemi Co., Ltd. assumes no liability for any applications or uses of its products and does not grant any licenses to its intellectual property rights or those of others. We also make no claims regarding non-infringement of third-party intellectual property rights that may arise from applications.

Due to technical requirements, our products may contain hazardous substances. For details, please contact your nearest sales office. This document replaces all previous information and may be updated. We reserve the right to make changes.