

Model Number

NCB2-12GM40-Z1

Features

- **2 mm flush**
- **2-wire DC**

Accessories


BF 12
Mounting flange, 12 mm

EXG-12
Quick mounting bracket with dead stop


Technical Data

General specifications		
Switching element function		DC NC
Rated operating distance	s_n	2 mm
Installation		flush
Output polarity		DC
Assured operating distance	s_a	0 ... 1.62 mm
Reduction factor r_{Al}		0.28
Reduction factor r_{Cu}		0.23
Reduction factor r_{304}		0.7
Nominal ratings		
Operating voltage	U_B	5 ... 60 V
Switching frequency	f	0 ... 800 Hz
Hysteresis	H	1 ... 10 typ. 5 %
Reverse polarity protection		reverse polarity tolerant
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 5 V
Operating current	I_L	2 ... 100 mA
Lowest operating current	I_m	2 mA
Off-state current	I_r	0 ... 0.5 mA typ.
Switching state indicator		all direction LED, yellow
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		cable PUR , 2 m
Core cross-section		0.14 mm^2
Housing material		Stainless steel 1.4305 / AISI 303
Sensing face		PBT
Degree of protection		IP67
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		Certified by China Compulsory Certification (CCC)

Dimensions



Electrical Connection



Release date: 2014-03-17 14:14 Date of issue: 2014-03-17 089254_eng.xml

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

PEPPERL+FUCHS:

BF18 GLV30-8-2500/47/73C NBB4-12GM50-A2-V1 NBB5-18GM50-E2 OBR5000-18GK40A-E2 NBB2-12GM50-E2 NBB2-8GM40-E0-V1 NBB2-12GM50-A2-V1 114642 MH4-2057 OBD450-18GK40A-E2 UB2000-F42-E6-V15 UBE800-F77-SE2-V31 24772 CCN15-30GS60-E2-V1 NBB0.8-5GM25-E2 NBB8-18GM50-E0 OBR12M-R100-2EP-IO-V31-L OQT150-R100-2EP-IO-V31-L OQT150-R101-2EP-IO-V31 UB800-18GM40-I-V1 S1SD-1AI-1U.1 134143 NBB0.8-4M25-E0 OBR2500-12GM40-E5 34441 NBB5-18GM50-A0 KLR-C02-2,2-2,0-K70 NBB1-4GM22-E2 WCS3-MH1