Foot mounting
CRHBN-12/16X2

Part number: 162999



General operating condition

Data sheet

Feature	Value
Size	12/16
Mounting position	Any
Corrosion resistance class (CRC)	4 - Particularly high corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Suitability for the production of Li-ion batteries	Metals with more than 5% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils
Product weight	107 g
Note on materials	RoHS-compliant
Mounting material	High-alloy stainless steel
Nut material	High-alloy steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

153307 NPQP-D-Q4-S8-FD-P10 NPQP-LQ-R18-Q4-FD-P10 NPQP-T-Q8-E-FD-P10 QS-10H-6 VABM-B10-25S-G38-10 VABM-B10-25S-G38-6-P3 NPQP-Y-R12-Q12-FD QSLL-G1/2-12 QSS-8-F SGS-M10X1,25 VBQF-U-G14-E 153151 NPQP-L-Q10-E-FD-P10 153269 DSBC-80-20-D3-PPSA-N3 QSF-3/8-8-B NPQP-LQ-R18-Q8-FD-P10 NPQP-Y-Q6-E-FD-P10 QSF-1/4-8-B QSY-6H-4 HGL-1/8-QS-6 NPQH-T-Q14-E-P10 153031 153367 CRVZS-0.4 QS-1/2-16 QS-1/8-8-I QSML-6 SASC-P4-A-M8-A