
SPX-12-8-SS

Ruland SPX-12-8-SS, 3/4" x 1/2" Rigid Coupling, 303 Stainless Steel, Two-Piece Clamp Style, 1 1/2" OD, 2 1/4" Length





Description

Ruland SPX-12-8-SS is a two-piece rigid coupling with 0.7500" x 0.5000" bores, 1 1/2" OD, and 2 1/4" length. SPX-12-8-SS has opposing hardware for a balanced design. Proprietary Nypatch® anti-vibration coating on hardware allows for even seating of the screw, repeated screw installations, prevents galling, and maintains high holding power. It eliminates the need to treat screws upon receipt greatly reducing installation time. Forged screws test beyond ANSI standards to ensure maximum holding power. Tightly controlled bore tolerance of +.002"/+.0005" is maintained. SPX-12-8-SS is made from 303 stainless steel with hardware of like material for consistent corrosion resistance. It is machined from solid bar stock that is sourced exclusively from North American mills and is RoHS3 and REACH compliant. SPX-12-8-SS is manufactured in our Marlborough, MA factory under strict controls using proprietary processes.

Product Specifications

Bore (B1)	0.7500 in	**Small Bore (B2)**	0.5000 in
B1 Max Shaft Penetration	1.125 in	**B2 Max Shaft Penetration**	1.125 in
Outer Diameter (OD)	1 1/2 in	**Bore Tolerance**	+0.0020 in / +0.0005 in
Length (L)	2 1/4 in	**Clearance Diameter (C) MAX**	1.842 in
Recommended Gap	0.094 in	**Recommended Shaft Tolerance**	+0.0000 in / -0.0005 in
Forged Clamp Screw	1/4-28	**Screw Material**	18-8 300 Series Stainless Steel with Nypatch®
Hex Wrench Size	3/16 in	**Screw Finish**	Bright
Seating Torque	110 lb-in	**Screw Location (R)**	0.545 in
Number of Screws	8 ea	**Rated Torque**	950 in-lb
Moment of Inertia	0.2859 lb-in^2	**Maximum Speed**	4,000 RPM
Full Bearing Support Required?	No	**Nypatch® Anti-Vibration Hardware?**	Yes
Zero-Backlash?	Yes	**Balanced Design**	Yes
Material Specification	Type 303 Austenitic, Non-Magnetic Bar	**Temperature**	-40°F to 350°F (-40°C to 176°C)
Finish Specification	Bright, No Plating	**Manufacturer**	Ruland Manufacturing
Country of Origin	USA	**Weight (lbs)**	0.853000
UPC	634529025765	**Tariff Code**	8483.60.8000
UNSPC	31163009		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65	⚠**WARNING** This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.		

Installation Instructions

1. Align the SPX-12-8-SS two-piece rigid coupling on the two shafts to be connected. There should be no misalignment.
2. Tighten the Nypatch® screws in two stages, starting with the inside screws. Using a 3/16 in torque wrench, tighten the inside screws to 55 lb-in which is half the recommended seating torque. Repeat the process for the outside screws, tightening to half the recommended seating torque.
3. Be sure to maintain the gap of 0.094 in between the two halves during installation.
4. Tighten the screws to the full recommended seating torque of 110 lb-in following the same pattern, starting with the inside screws first.
5. For optimum results do not exceed the shaft penetration length of 1.125 in.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Ruland Manufacturing:

ENCL20-6MM-A OCT12-4-A OF-MSP-20-F FHD-MCL-25-F MOCT57-25-A FHD-MCL-35-AN
LV-MSP-25-SS MJS33-12-A MSPX-12-12-F MTCL-12-1.75-F MWC30-10-10-SS OD36/57-AT
MRSC13-5-5-A MSP-22-F ENSP20-10MM-A ENSP30-12MM-A MCL-4-F MOCT19-5-A MQCL-8-A
MSP-12-P MJC57-25-A MRLC16-8-8-A MSPC-16-16-F MSPX-8-8-F FHD-MCL-30-SS FSMR32-13-12-A
MJS25-8-A MRSC25-5-5-A MSP-6-SS MSPX-16-16-F