



Datasheet for part number MDM-21SH003M7

Our Catalog Part Number: MDM-21SH003M7			
Brand: Cannon	Product Category: Micro	Product Line: Micros	Series: MICRO

Product Datasheet	
Series	Micro "D" Metal Shell
Arrangement	21 Contact
Gender	Socket
Contact Material	gold plated copper alloy
Contact Typ	crimp
Contact Resistance	8 milliohms max.
Termination Type	18" Min, M16874/4 #26AWG, Colored Code
Shell Material	Aluminum
Shell Finish	Yellow Chromate/Cadmium over Nickel
Insulator Material	contact size 9 to100 = liquid crystalline polymer, contact arrangements 7C2 or 24C4 = Diallyl phthalate
Hardware	Jackpost, M83513/5-07
Coupling	Jackscrew Coupling
Current Rating	3 A max.
Dielectric Withstanding Voltage	600 VAC at sea level 150 VAC at 70,00' altitude
Insulator Resistance	5000 megohms min.
Thermal Shock	-55°/+125°
Physical Shock	50 G's, 3 axes, 6 milisecond duration sawtooth pulse
Vibration	20G's, 10-2000 Hz. 12 hours
Durability	500 cycles of mating and unmating, 500 CPH max.
Moisture Resistance	Insulator resistance > 100 megohms
SaltSpray	48 hours

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

ITT:

[DBA13W3SA197F0](#) [M24308/4-2F](#) [M83513/03-E03C](#) [MDM-51SSB-A174](#) [MDM-BT 51TE-SJS-CAD-](#)
[MS3106E10SL-3S](#) [132066-1400](#) [980-2000-347](#) [CA3100E24-28SXB](#) [CA3101E28-20PF187](#) [DL1-C/C](#)
[MS3101E14S5S](#) [CA3102E20-15SF80F0](#) [CA3102E20-33P-F80-F0](#) [M24308/23-45P](#) [MDM-25SSB-A174](#)
[057-8511-000](#) [CA06R2410PZF80](#) [CA3101E28-21PF80F42](#) [KPSE06F24-61S](#) [KPT06A-20-24P](#) [1303420001](#)
[132066-2202](#) [MKJ1A6F6-7SA](#) [192900-0238](#) [CA3100E24-10PBF8008](#) [CA3100E24-28SWB02](#)
[CA3101E16S-1P-B-01](#) [CA3102R20-8P](#) [MS3116E8-3P](#)