Rod clevis
CRSG-M12X1,25

Part number: 13570



General operating condition

Data sheet

Feature	Value
Size	M12x1.25
Mounting position	Any
Based on norm	DIN 71752 ISO 8140
Threaded connection	Internal thread M12x1.25
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Metals with more than 5% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils
Ambient temperature	-40 °C ... 150 °C
Product weight	162.8 g
Rod clevis material	High-alloy steel
Note on materials	RoHS-compliant
Bolt material	High-alloy steel
Nut material	High-alloy steel
Fuse material	High-alloy steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

QSML-6 SGS-M10X1,25 QSY-6H-4 NPQP-LQ-R18-Q4-FD-P10 NPQP-Y-Q6-E-FD-P10 VABM-B10-25S-G38-6-P3 153151 153307 QS-1/8-8-I QSF-3/8-8-B QSS-8-F 153031 153269 HGL-1/8-QS-6 NPQP-Y-R12-Q12-FD QSF-1/4-8-B QSLL-G1/2-12 VABM-B10-25S-G38-10 153367 DSBC-80-20-D3-PPSA-N3 NPQH-T-Q14-E-P10 NPQP-D-Q4-S8-FD-P10 NPQP-LQ-R18-Q8-FD-P10 CRVZS-0.4 SASC-P4-A-M8-A QS-10H-6 VBQF-U-G14-E NPQP-L-Q10-E-FD-P10 NPQP-T-Q8-E-FD-P10 QS-1/2-16