Short-stroke cylinder
ADVC-10-10-A-P-A

Part number: 188077





General operating condition

Data sheet

Feature	Value
Stroke	10 mm
Piston diameter	10 mm
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Mode of operation	Double-acting
Structural design	Piston Piston rod
Position sensing	For proximity sensor
Symbol	00991217
Operating pressure	0.1 MPa ... 0.8 MPa
Operating pressure	1 bar ... 8 bar
Operating pressure	14.5 psi ... 116 psi
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-20 °C ... 80 °C
Theoretical force at 6 bar, retracting	40 N
Theoretical force at 6 bar, advancing	47 N
Moving mass	3.7 g
Product weight	35 g
Type of mounting	Optionally: With through-hole With accessories
Pneumatic connection	M5
Note on materials	RoHS-compliant
Cover material	Wrought aluminum alloy Anodized
Seals material	NBR TPE-U(PU)
Housing material	Wrought aluminum alloy Anodized
Piston rod material	High-alloy steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

QSF-1/4-8-B NPQP-LQ-R18-Q8-FD-P10 QS-1/2-16 VBQF-U-G14-E 153269 DSBC-80-20-D3-PPSA-N3 QS-1/8-8-I QSF-3/8-8-B QSY-6H-4 VABM-B10-25S-G38-10 SASC-P4-A-M8-A VABM-B10-25S-G38-6-P3 QSS-8-F 153307 153367 HGL-1/8-QS-6 NPQP-LQ-R18-Q4-FD-P10 NPQP-Y-Q6-E-FD-P10 QS-10H-6 153151 NPQP-T-Q8-E-FD-P10 NPQP-Y-R12-Q12-FD QSLL-G1/2-12 153031 NPQP-D-Q4-S8-FD-P10 NPQP-L-Q10-E-FD-P10 QSML-6 SGS-M10X1,25 CRVZS-0.4 NPQH-T-Q14-E-P10