General Description

The NVD6824NLT4G-VF01 use advanced SGT MOSFET technology to provide low RDS(ON), low gate charge, fast switching and excellent avalanche characteristics.

This device is specially designed to get better ruggedness.



TO-252-2L

General Features

V_{DS} = 100V I_D =40 A

$R_{DS(ON)}$ < 23mΩ @ V_{GS}=10 V



N-SGT MOSFET

Applications

Consumer electronic power supply
Motor control
Synchronous-rectification
Isolated DC
Synchronous-rectification applications

Package Marking and Ordering Information

Product ID	Pack	Brand	Qty(PCS)
NVD6824NLT4G-VF01	TO-252-2L	HXY MOSFET	2500

Absolute Maximum Ratings at T_j=25℃ unless otherwise noted

Symbol	Parameter	Value	Unit
VDS	Drain source voltage	100	V
VGS	Gate source voltage	±20	V
ID	Continuous drain current[1], T_C=25 ℃	40	A
ID, pulse	Pulsed drain current[2], T_C=25 ℃	100	A
P_D	Power dissipation[3], T_C=25 ℃	27	W
EAS	Single pulsed avalanche energy[5]	16	mJ
Tstg，Tj	Operation and storage temperature	-55 to 150	℃
RθJC	Thermal resistance, junction-case	4.65	℃/W
RθJA	Thermal resistance, junction-ambient[4]	62	℃/W

Electrical Characteristics at T_j=25 ℃ unless otherwise specified

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 250μA	100	-	-	V
I_{DSS}	Drain-Source Leakage Current	V_{DS} = 80V, V_{GS} = 0V	-	-	1	μA
I_{GSS}	Gate to Body Leakage Current	V_{DS} = 0V, V_{GS} = ±20V	-	-	±100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250μA	1.2	1.8	2.6	V
$R_{DS(on)}$	Static Drain-Source On-Resistance	V_{GS} = 10V, I_D = 15A	-	20	23	mΩ
		V_{GS} = 4.5V, I_D = 10A	-	-	33	mΩ
g_{fs}	Forward Threshold Voltage	V_{DS}= 10V, I_D= 20A	-	22	-	S
R_g	Gate Resistance	V_{DS} = V_{GS}=0V, f = 1.0MHz	-	1.62	-	Ω
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS} = 50V, V_{GS} = 0V, f = 1.0MHz	-	822	-	pF
C_{oss}	Output Capacitance		-	310	-	pF
C_{rss}	Reverse Transfer Capacitance		-	23.5	-	pF
Switching Characteristics						
Q_g	Total Gate Charge	V_{DS}= 50V, I_D = 20A, V_{GS} = 10V	-	22.7	-	nC
Q_{gs}	Gate-Source Charge		-	6.2	-	
Q_{gd}	Gate-Drain(“Miller”) Charge		-	5.3	-	
$t_{d(on)}$	Turn-On Delay Time	V_{DS} = 50V, I_D = 20A, R_G = 3Ω, V_{GS}=10V	-	15	-	ns
t_r	Turn-On Rise Time		-	3.2	-	
$t_{d(off)}$	Turn-Off Delay Time		-	30	-	
t_f	Turn-Off Fall Time		-	7.6	-	
Diode Characteristics						
I_S	Continuous Source Current		-	-	40	A
V_{SD}	Diode Forward Voltage	I_S=20A . V_{GS} = 0V	-	0.88	1.0	V
t_{rr}	Reverse Recovery Time	I_{SD}=20A, dI_{SD}/dt=100A/μs	-	45	-	ns
Q_{rr}	Reverse Recovery Charge		-	59	-	nC

Notes:

1. The value of $R_{\theta JC}$ is measured in a still air environment with TA =25°C and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.

2. The power dissipation P_D is based on $T_{J(MAX)}$=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

3. Single pulse width limited by junction temperature $T_{J(MAX)}$=150°C.

4. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to case $R_{\theta JC}$ and case to ambient.

5. The maximum current rating is package limited.

6. The EAS data shows Max. rating. The test condition is V_{DS}=50V,V_{GS}=10V,L=0.5mH

Electrical Characteristics Diagrams



Figure 1. Output Characteristics



Figure 2. Transfer Characteristics



Figure 3. Drain-to-Source On Resistance vs Drain Current



Figure 4. Body Diode Forward Voltage vs Source Current and Temperature



Figure 5. Capacitance Characteristics



Figure 6. Gate Charge Characteristics



Figure 7. Normalized Breakdown Voltage vs Junction Temperature



Figure 8. Normalized On Resistance vs Junction Temperature



Figure 9. Maximum Continuous Drain Current vs Case Temperature



Figure 10. Maximum Power Dissipation vs Case Temperature



Figure11. Drain-to-Source On Resistance vs Gate



Figure 12. Maximum Safe Operating Area



Figure 13. Maximum Effective Transient Thermal Impedance, Junction-to-Case

TO-252-2L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.660	0.860	0.026	0.034
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	0.483 TYP.		0.190 TYP.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.800	10.400	0.386	0.409
L1	2.900 TYP.		0.114 TYP.	
L2	1.400	1.700	0.055	0.067
L3	1.600 TYP.		0.063 TYP.	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.350 TYP.		0.211 TYP.	

Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HXY MOSFET:

SS10100 SS5150B TPSMB28A-VR HOPA2340UA SQJA04EP-T1_BE3 P6SMB200A P6SMB33CA US2M
HC4D20120A SS510C TPSMB100CA-VR MMBT3904T SS1045 HXY2101EI HXY2300MI BZT52C13
HMCP602-I/SN HC3D10170A HT7540-1 MAX487ESA BZT52C3V3S DTC143ZE HAD8542ARZ
HESDNC5VB1AF-B PESD5V0S1BB HT7150 HXY8205ES IRLML6246PBF P6SMB36CA SD15C