GWAYAR-P19WDDO-ROOL

easy_clean

type_gw


General information

Part number	GWAYAR-P19WDDO-ROOL
Termination	solder
Size	1,5
Locking principle	break , push
Coding	a_key_amc
Cable Diameter	cable_amc_A



Illustrations may differ from original product.
Dimensions, unless otherwise specified, in mm.


CODING:A



POSITIONS: 19 positions



PANEL CUT OUT:



The pin layout corresponds to the view on the termination area

Contact insert description

Number of contacts	19
Contact type	flat_contact
Contact diameter	06mm
Insulator material	peek
Wire cross section	26_awg
Termination	solder
Termination diameter	065mm

reverse_gender_on_request

Technical information

Nominal current single contact	02_a	iec_60512_5_2
Nominal current insert	0,9 A	vde_0298_4
Test voltage	06_kv_ac	eia_364_20f

safety_text

Mechanical and environmental data

Degree of protection*	ipsk8_ip6k9k
Operating temperature	51_125_c
Mating cycles	5000

mated

Material and surface treatments

Housing	ruthenium
Contact	cu_alloy_gold

safety_text_2
ul_text
illustrative_text

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

ODU:

S10L0C- P10MCC9-5600 S11MA7-P07MFD0-5230 S12YAR-P26XCD0-0000 G11L0C- P08LFG0-0000
GK0WBM-P09WMM0-000L S10L0C- P03MJG0-5600 S20K0C-P09MCC0-500S S2CLAC-P02MCC0-2500
S41M07-P08MFG0-397S GKCWAC-P07QB00-000L K11K0C-P07LFG0-5000 S11M07- P05MJG0-5220
S11MA7-P04MJG0-3950 G51L0C- P02LPH0-0000 GC0WAM-PD1UM00-000L K11M07- P06LFD0-5250
S11MA7-P06MFD0-6540 A10WDM-P09XMM0-0000 S11L0C- P04MJG0-4200 S21K0C-P02MPH0-550S
G51M07- P12LCC9-0070 G80YAR-P09UC00-000L G80YBR-P10WCD0-000L K11MA7-P08LFD0-3980
K11YAR-P10XDD0-R000 S11MA7-P05MJG0-5240 G51LFC-P10QC00-A000 K11YBR-P16XDD0-R000
S21L0C- P04MJG0-720S K11M07- P04LJG0-3980