
PRODUCT NUMBER: 7466-0-15-15-21-27-04-0

www.mill-max.com
DATA SHEET





7466-0-15-15-21-27-04-0 SPECIFICATIONS

General Info	
Description[1]:	Receptacle With A Standard Tail
Mounting Feature:	Press-Fit into a Non-Plated Through Hole (NPTH)
Mounting Hole:	.043" (1,092mm)
Alternate Mounting[2]:	Through-Hole Soldertail Mount
Pin Diameter Range:	.015"-.022" (0,381-0,559mm)
Packaging:	Packaged in Bulk
RoHS[3]:	Yes
Product Lifecycle[4]:	Active

Materials	
Shell Material [5]:	Phosphor Bronze
Shell Plating[6]:	10 µ" Gold over Nickel
Contact Plating[7]:	30 µ" Gold over Nickel


Technical Specs	
Mechanical life (Durability)[8]:	1,000 Cycles Minimum
Operating Temperature Range[9]:	-55/+125° C
Current Rating[10]:	3A @ 10°C Temperature Rise
Contact Resistance[11]:	10 mΩ Max
Shock[12]:	No Elect. Discontinuity > 1µs @ 50g
Vibration[13]:	No Elect. Discontinuity > 1µs @ 10-2000HZ, 20 G


(c)2024 Mill-Max Mfg Corp. | 516-922-6000
190 Pine Hollow Road, Oyster Bay, NY 11771

NOTES:

1. Standard Tolerances:
   Lengths +/-.005" (0,13)
   Diameters: +/-.002" (0,051)
   Angles: +/- 2°
2. For through-hole solder mounting of this part, the suggestion is to make the finished hole size, at its minimum, .004" larger than the diameter being soldered into the mounting hole.
3. Mill-Max products labeled with the RoHS symbol are compliant with all three ROHS Directives. All of our products previously described as RoHS (2002/95/EC) and RoHS-2 (2011/65/EC) are also compliant with RoHS-3 (2015/863/EU).
4. Part is Active and in Production, No Scheduled Obsolescence
5. Phosphor Bronze Alloy 544 per ASTM-B139
6. GOLD per ASTM B 488, Type 1 (99.7% min. gold), Code C (130-200 HK {Knoop hardness}); NICKEL per ASTM B 689, Type 2 (Bright),
7. GOLD per ASTM B 488, Type 1 (99.7% min. gold), Code C (130-200 HK {Knoop hardness}), NICKEL per ASTM B 689, Type 2 (Bright)
8. Receptacles are capable of 1,000 Minimum insertion/extraction cycles for a broad range of applications. Mating pin size, shape and finish, along with application specific variables, will affect the life of a receptacle contact.
9. Per IEC 60512-11-(4,-9,-10,-12)
10. Per IEC 60512-5-1, Current Carrying Capacity (evaluated at 10˚ C Temp. Rise)
11. Per EIA-364-23C, Low Level Contact Resistance
12. Per IEC 60512-6-3: Test 6c: Shock
13. Per IEC 60512-6-4: Test 6d: Vibration (sinusoidal)

CONTACT:





The insertion / extraction force characteristics above were derived using a 30 microinch gold-plated contact and polished steel gauge pins having a bullet-shaped tip.
The curves represent typical average values; they are best used to compare the differences between similar size contacts and to guide you in selecting one that is suitable for your application.
Your results may vary, so for your specification, we encourage you to obtain complimentary samples for your evaluation.

Material	Beryllium Copper	**Current Rating (amps)**	3.00
Fingers	3	**Compliancy (δ)**	0.004
Length	.080" (2,032mm)	**Maximum Current**	6A @ 30º C Temp. Rise

Maximum Operating Temp @ Max Current	120.00˚ C	**20% De-rated Maximum Current**	4.80A
Contact Group	A		

ADDITIONAL NOTES AND SPECIFICATIONS

In the interest of improved design, quality and performance , Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

RELATED LINKS AND DOCUMENTS

Engineering Notebook: (https://www.mill-max.com/engineering-notebooks/pin-receptacles/the-backbone-of-your-interconnect-system)
Environmental Compliance: (https://www.mill-max.com/rohs)

(c)2024 Mill-Max Mfg Corp. | 516-922-6000
190 Pine Hollow Road, Oyster Bay, NY 11771

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

MILL-MAX:

0327-0-15-01-34-27-10-0 0566-1-15-15-21-14-10-0 0988-0-15-20-89-14-11-0 311-93-164-41-001000
855-22-010-10-001101 110-13-306-41-001000 110-41-328-41-001000 110-93-324-41-001000
319-10-107-30-054000 380-10-105-10-003000 855-22-008-10-001101 878-22-004-10-011101
110-47-314-41-001000 1656-0-57-15-00-00-03-0 3157-0-00-21-00-00-03-0 940-44-044-17-400000
142-10-324-00-592000 3735-0-19-15-34-27-10-0 0156-0-18-80-30-84-04-0 110-99-324-41-001000
342-10-104-00-594000 814-22-004-30-004101 858-10-006-10-002000 0914-1-15-20-77-14-11-0
342-10-101-00-591000 0880-1-15-20-82-14-11-0 0908-0-15-20-75-14-11-0 801-43-022-10-001000
813-22-004-30-002101 917-93-103-41-005000