
Compact air cylinder
ADVUL-20-5-P-A

Part number: 156858





General operating condition

Data sheet

Feature	Value
Stroke	5 mm
Piston diameter	20 mm
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Structural design	Piston Piston rod
Position sensing	For proximity sensor
Symbol	00991737
Variants	Piston rod at one end
Protection against torsion/guide	Guide rod with yoke
Operating pressure	0.1 MPa ... 1 MPa
Operating pressure	1 bar ... 10 bar
Mode of operation	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-20 °C ... 80 °C
Impact energy in the end positions	0.14 J
Theoretical force at 6 bar, retracting	141 N
Theoretical force at 6 bar, advancing	188 N
Type of mounting	Optionally: With through-hole With accessories
Pneumatic connection	M5
Flange screws material	Steel, galvanized
Cover material	Wrought aluminum alloy
Material of dynamic seals	NBR TPE-U(PU)
Piston rod material	High-alloy stainless steel
Material of cylinder barrel	Wrought aluminum alloy

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

DFM-63-100-P-A-KF DSBC-40-160-D3-PPSA-N3 QSLV-G1/8-8 QS-G1/8-6-I VABM-L1-14W-G14-4-GR VABM-B10-25S-G38-4-P3 NPQH-T-G38-Q8-P10 NPQP-D-R38-Q10-FD-P10 QSLV-G1/2-12-I 153034 DSBC-32-40-D3-PPVA-N3 DSBC-63-320-D3-PPVA-N3 VABM-L1-18S-G38-10 DSBC-32-50-D3-PPVA-N3 VABM-B10-20S-G14-6 NPQH-D-Q12-Q8-P10 NPQH-D-S14-Q8-P10 QS-G3/8-12 VABM-B10-25S-G38-6 SPTW-P16R-G14-A-M12 HGL-1/8-B QSL-1/4-4 QSL-12 QSLV-G1/4-6 SEA-3GS-M8-S DSBC-40-50-D3-PPSA-N3 DSBC-50-20-D3-PPSA-N3 NPQH-D-Q14-E-P10 NPQP-D-R14-Q10-FD-P10 VABM-L1-10HW-G18-4-GR