Heatsinks f.cool

- Profile heatsinks and fluid coolers
  - Standard extruded heatsinks
  - Extruded heatsinks for lock-in retaining spring
  - Extruded heatsinks for PCB mounting
  - Extruded heatsinks for DC/DC converter
  - Retaining springs for transistors
  - U-Extruded heatsinks
  - Die-cast heatsinks
  - Fin coolers
  - Fluid coolers
  - Aluminium flat-, quadrangular-, angled-, U- & T-profiles
- Heatsinks and active heatsinks for processors
- Finger-shaped heatsinks
- Cooling aggregates
- Accessories for electronic components

Cases f.case

Connectors f.con

Standard extruded heatsinks

SK 04 100 SA

97 x 25 mm, with guideway for cover plates or blanks

add to request



Features | Technical Drawing | Service

width	97 mm
heigth	25 mm
plate thickness	4 mm
lengths	100 mm
R_{th}	1.3 - 2.8 K/W
drilling pattern	TO 3 CB SSR 1 SSR 2
surface	black anodised

Fischer Elektronik GmbH & Co. KG
Nottebohmstraße 28, D - 58511 Lüdenscheid
Ph: +49 (0) 23 51 / 4 35 - 0, info@fischerelektronik.de

Mohamed Zaky
RS REJ.xlsx

Internet 110%

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Fischer Elektronik:

BLY 1 50 Z SK68-50SA LA 17/200 24V SK 88 50 SA WKT 300 MS 53 3 FK 245 MI 247 H LA 7/150 24V SL 22 112 72 G CC 35 67 100 ME FK 224 SA P SIP P SIP SK 04 100 SA SL 11 190 36 G FK 232 220 SA FK 240 SA 220 V SK 104 38,1 STS KL35050 SK 85 100 SA SL22 124-16G THFK247 TUF 80 42 100 SA FK 244 13 D2 PAK TO-263 (D2PAK) FK 247 220 MI TO 220 LA ICK 17 X17 W 12V SK 85 50 SA SK0937,5TO220 WLK 5 SK 198 1000 AL SK 58 50 SA SK68-37,5-SA