Push-in L-fitting
QSLF-1/8-8-B

Part number: 153276

FESTO



General operating condition

Data sheet

Feature	Value
Size	Standard
Nominal width	6 mm
Mounting position	Any
Design	L-shape
Pack size	10
Structural design	Push-pull principle
Operating pressure for entire temperature range	-0.095 MPa ... 0.6 MPa
Operating pressure for entire temperature range	-0.95 bar ... 6 bar
Operating pressure for entire temperature range	-13.775 psi ... 87 psi
Temperature-dependent operating pressure	-0.095 MPa ... 1.4 MPa
Temperature-dependent operating pressure	-0.95 bar ... 14 bar
Temperature-dependent operating pressure	-13.775 psi ... 203 psi
Information on operating pressure	Water: max. 0.6 MPa at max. 50 °C
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-] Water (liquid, ice-free)
Information on operating and pilot media	Operation with oil lubrication possible
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Cleanroom class	Class 4 according to ISO 14644-1
Ambient temperature	-10 °C ... 80 °C
Nominal tightening torque	7 Nm
Tolerance for nominal tightening torque	± 20%
Product weight	16 g
Type of mounting	External hexagon, AF 14
Pneumatic connection 1	Internal thread G1/8
Pneumatic connection 2	for pneumatic tubing outside diameter 8 mm
Releasing ring color	Blue
Material of screwed plug	Brass, nickel-plated
Note on materials	RoHS-compliant
Housing material	PBT
Releasing ring material	POM
Material of tubing seal	NBR
Material of tube retaining claw	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

QS-1/8-8-I QSML-6 QS-10H-6 153031 QSS-8-F VABM-B10-25S-G38-10 NPQP-T-Q8-E-FD-P10 DSBC-80-20-D3-PPSA-N3 NPQH-T-Q14-E-P10 153269 153367 HGL-1/8-QS-6 NPQP-D-Q4-S8-FD-P10 VBQF-U-G14-E CRVZS-0.4 NPQP-LQ-R18-Q8-FD-P10 QS-1/2-16 QSLL-G1/2-12 QSY-6H-4 VABM-B10-25S-G38-6-P3 QSF-1/4-8-B QSF-3/8-8-B SASC-P4-A-M8-A SGS-M10X1,25 NPQP-LQ-R18-Q4-FD-P10 153151 NPQP-L-Q10-E-FD-P10 NPQP-Y-Q6-E-FD-P10 153307 NPQP-Y-R12-Q12-FD