## MLE96-24DC-P

**Class 2 Electronic Phase cut Dimmable**

Outdoor Plastic Suitable For Dry And Damp Location Enclosure


Single Circuit: **24VDC 120Hz**


Total Wattage: **96W max**


Input Voltage: **120V 50/60Hz**

www.emcod.com

**Conforms to UL STD. 8750 and 1310**
**Certified to CSA**
**STD. C22.2 № 223**
**model MLE96-24DC-P**






### Transformer

Dimmable with compatible MLV, ELV, CL dimmers, please refer to list on emcod.com
Temperature class B(130°C)
Input leads are 18AWG 600V
Output leads are 18AWG 300V
Leads max. operational temperature is 105°C

### Housing

The actual transformer 96W is encapsulated in the enclosure
The enclosure is Plastic suitable for dry and damp location, fit in 4" junction box, IP20 rated
Enclosure Temperature does not exceed 90°C at 45°C ambient and fully loaded
Dimensions (inch): H = 1.77, W = 3.34, D = 1.02
Weight (LBs): 0.4

### Electrical Parameters

| | |
|---|---|
| Input Voltage: | **120V 50/60Hz** |
| Max. input current at full load: | **1A** |
| Output voltage without load: | **25.5VDC** |
| Output voltage fully loaded: | **23.5VDC** |
| Max. Total Wattage: | **96W** |
| Max. Output Current: | **4A** |
| Efficiency: | **89%** |

**Mailing Address: 646 Flinn Ave. Unit B, Moorpark , CA 93021  Tech support: Arik Nirenberg phone: 818-904-3309**
**Fax: 818 904 3327  info@emcod.com  techsupport@emcod.com**

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## Emcod:

MLE96-24DC-P