DATA SHEET

COAXIAL ADAPTER, N, 50 Ohm, Bulkhead, jack / jack (female / female)

34_N-50-0-1/133_N

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration		
Interface type	Gender	Standard
N	jack (female)	IEC 61169-16_MIL-STD-348A/304_CECC 22210
N	jack (female)	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data		
N		
Piece parts	**Material**	**Plating**
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating
N		
Piece parts	**Material**	**Plating**
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Electrical data	
Impedance	50 Ω
Interface frequency	18 GHz
VSWR	DC - 12.4 GHz (≤ 1.06 + 0.17 f GHz)

COAXIAL ADAPTER, N, 50 Ohm, Bulkhead, jack / jack (female / female)

34_N-50-0-1/133_N

Mechanical data	
Weight	0.0486 kg
Mating cycles	500

Environmental data	
Operation temperature	-65 °C ... 165 °C

Ordering Information Table

Item number	Item description	Packaging type
22542435	34_N-50-0-1/133_NE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2108 / Date of publication: 27.05.2024 / uncontrolled copy

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Huber+Suhner:

1399.17.0210 1399.31.0020 6620_SMA-50-2/199_NE 84118385 23002145 6601_PC185-50-1/199_NE 85201112 G032D/Nm/SMAm/1000 RADOX 125 0.75 MMÂ² RED 11_SMC-50-2-10/111_NE 33_PC24-SK-50-2/199_NE 6806.19.A MINIBEND R-10 RG_196_A/U MINIBEND R-12 PCRS_LCMX_LCMX_O421T_30.0_LL 11MMBXEF31616MMBX/300 11_TNC-50-3-116/133_NE 12012090 1399.17.0231 12535682 MINIBEND R-8 Minibend L-10 24_SMA-50-2-15/111_NH 22511964 23000457 84093961 G032D/BNCm/BNCm/1000 16_MMCX-50-2-4/111_OH G_03130_HT-01