332BS6

Wall mounted inlet

2CMA193322R1000



Wall mounted inlet, earthing sleeve position 6h, rated current 32A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Red

GENERAL

Product Name	Wall mounted inlet
Product ID	2CMA193322R1000
Function	Wall mounted inlet
EAN	7392696933223
Catalog Description	Surface inlet, 6h, 32A, IP44, 3P+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2421523
E-Number Norway	1542413
E-Number Sweden	E2417186
Standards	IEC 60309-1, -2
RoHS Status	Following EU Directive 2011/65/EU

TECHNICAL

Product Main Type	EBS
Color	Red
Number of Poles	4
Clock Position	6Hour
Rated Current	32 ampere
Rated Voltage	380 ... 415 volt
Frequency	50 hertz|60 hertz
Degree of Protection	IP44
Cable Cross-Section	2.5...10 mm²
Housing Material	Plastic (PA)
Plug Angle	Angled
Product Group	Easy&Safe

DIMENSIONS

Product Net Width	85 millimetre
Product Net Height	116 millimetre
Product Net Length	163 millimetre
Product Net Depth	163 millimetre
Product Net Weight	0.27 kilogram

PACKAGING

Package Width	188 millimetre
Package Height	428 millimetre
Package Gross Weight	2.7 kilogram
Package Length	175 millimetre
Package Units	box 10 piece

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Amphenol:

67996-204HLF 68001-108HLF 86093968191755E3LF RJE061661210 68002116HLF 70234-112LF 91614-403ALF 69192-408HLF 70218-1116LF 70430-164LF 86093967896755LF CD15S13E4RV09LF DAPO15S365TLF DCMF37P DEM09P032N 54202-G0805CLF 68000-236HLF 86093488314745V1LF 86093968813H45V1LF 86130202123355E1LF 95157-140LF 54202-S08-07LF 68001-200HLF LD25S33E4GV00LF RJSBE5080C2 65781-158 863013A D15P13A6RV12LF LD15P33E4GV00LF 76384-316LF