
# Proximity sensor
# SIEH-M12B-PS-S-L

Part number: 150451






General operating condition

## Data sheet

| Feature | Value |
|---|---|
| Conforms to standard | EN 60947-5-2 |
| Symbol | 00991701 |
| Certification | C-Tick<br>c UL us - Listed (OL) |
| CE marking (see declaration of conformity) | As per EU EMC directive |
| Rated operating distance | 4 mm |
| Assured operating distance | 3.24 mm |
| Reduction factors | Aluminum = 0.4<br>Stainless steel St 18/8 = 0.8<br>Copper = 0.4<br>Brass = 0.5<br>Steel St 37 = 1.0 |
| Ambient temperature | -25 °C ... 70 °C |
| Repetition accuracy under constant conditions | 0.2 mm |
| Switching output | PNP |
| Switching element function | N/O contact |
| Hysteresis | ≤0.36 mm |
| Max. switching frequency | 2500 Hz |
| Max. output current | 200 mA |
| Voltage drop | ≤2 V |
| Inductive protective circuit | Installed |
| Short-circuit protection | Pulsed |
| DC operating voltage range | 10 V ... 30 V |
| Residual ripple | ± 10% |
| Idle current | ≤10 mA |
| Reverse polarity protection | for all electrical connections |
| Electrical connection | 3-pin<br>M12x1<br>Plug |
| Size | M12 |
| Type of mounting | With lock nut |
| Mounting type | Flush |
| Product weight | 30 g |
| Housing material | Brass<br>PBTP<br>Nickel-plated |
| Switching status indication | LED yellow |
| Ambient temperature with flexible cable installation | -5 °C ... 70 °C |

| Feature | Value |
|---|---|
| Degree of protection | IP65<br>IP67 |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Selection of additional sensor information | With increased switching distance |
| Electrical output | PNP |
| Selection of sensor version | Standard |

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## FESTO:

N-1/8-P-6 NPQP-LQ-R18-Q4-FD-P10 QS-1/2-16 SNC-63 DSBC-80-250-D3-PPSA-N3 DSNU-12-60-P-A NPQP-Y-R12-Q12-FD PUN-H-4X0,75-TBL QSML-3 QSS-8-F NPQH-T-G38-Q8-P10 NPQP-D-Q4-S8-FD-P10 QH-1 1/2 SPTE-V1R-Q3-V-2.5K DSBC-50-20-D3-PPSA-N3 QSLL-1/4-4 VBQF-U-G14-E NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q8-FD-P10 NPQP-Y-Q6-E-FD-P10 CRVZS-0.4 QSLV-G1/4-6 QSML-6 DFM-63-100-P-A-KF DSBC-32-40-D3-PPVA-N3 DSBC-32-50-D3-PPVA-N3 DSBC-80-320-D3-PPVA-N3 DSBC-63-320-D3-PPVA-N3 MSFW-110-50/60-DS VABM-L1-18W-G38-8-G