


Inductive sensor

NMB1,5-8GM23-Z3-C-FE-850MM-V1

- 1.5 mm flush
- 2-wire DC
- Stainless steel sensing face
- Weld field immune
- Weld slag resistant coating
- Ferrous targets

Dimensions



Technical Data

General specifications		
Switching function		Normally open (NO)
Output type		Two-wire
Rated operating distance	s_n	1.5 mm
Installation		flush
Output polarity		DC
Assured operating distance	s_a	0 ... 1.215 mm


Release date: 2024-05-28 Date of issue: 2024-06-08 Filename: 908880_eng.pdf

Technical Data


Actuating element		Ferrous targets
Reduction factor r_{Al}		0
Reduction factor r_{Cu}		0
Reduction factor r_{304}		0.4 - 0.7
Reduction factor r_{St37}		1
Reduction factor r_{Brass}		0
Output type		2-wire
Nominal ratings		
Operating voltage	U_B	6 ... 30 V DC
Switching frequency	f	0 ... 5 Hz
Hysteresis	H	3 ... 15 typ. 5 %
Reverse polarity protection		reverse polarity tolerant
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 4.5 V DC at 30 mA
Operating current	I_L	2 ... 100 mA
Lowest operating current	I_m	2 mA
Off-state current	I_r	≤ 0.6 mA
Switching state indicator		LED, red
Mag. Field strength, AC fields		250 mT
Mag. Field strength, DC fields		250 mT
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		fixed cable with plug
Housing material		Xylan coated - Stainless steel 1.4305 / AISI 303
Sensing face		Xylan coated - Stainless steel 1.4305 / AISI 303
Degree of protection		IP67
Connector		
Threading		M12 x 1
Tightening torque		0.6 Nm
Number of pins		3
Cable		
Cable diameter		4.8 mm ± 0.2 mm
Material		POC
Color		orange
Number of cores		4
Core cross section		0.34 mm^2
Length	L	850 mm
Dimensions		
Length		23 mm
Diameter		8 mm

Release date: 2024-05-28 Date of issue: 2024-06-08 Filename: 908880_eng.pdf

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)

Release date: 2024-05-28 Date of issue: 2024-06-08 Filename: 908880_eng.pdf

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

PEPPERL+FUCHS:

CCN15-30GS60-E2-V1 NBB0.8-4M25-E0 NBB5-18GM50-A0 WCS3-MH1 OQT150-R100-2EP-IO-V31-L 114642 GLV30-8-2500/47/73C NBB1-4GM22-E2 NBB2-12GM50-A2-V1 NBB2-8GM40-E0-V1 NBB4-12GM50-A2-V1 24772 MH4-2057 NBB8-18GM50-E0 OBD450-18GK40A-E2 S1SD-1AI-1U.1 BF18 UB800-18GM40-I-V1 UBE800-F77-SE2-V31 NBB5-18GM50-E2 OBR12M-R100-2EP-IO-V31-L OBR2500-12GM40-E5 OBR5000-18GK40A-E2 UB2000-F42-E6-V15 KLR-C02-2,2-2,0-K70 NBB0.8-5GM25-E2 NBB2-12GM50-E2 134143 34441 OQT150-R101-2EP-IO-V31