N-channel Enhancement Mode Power MOSFET

Features

- V_{DS}= 80 V, I_D= 95A
  RDS(ON) < 6 mΩ @ VGS = 10V
  RDS(ON) < 7 mΩ @ VGS =4.5V

General Features

- Advanced Trench Technology
- Provide Excellent RDS(ON) and Low Gate Charge
- Lead Free and Green Available

100% UIS TESTED!
100% ΔVds TESTED!

RoHS



TO-252-2L Top View



Pin Assignment



Schematic Diagram

Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	80	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous	I_D	95	A
Drain Current-Continuous(T_C=100℃)	I_D (100℃)	67	A
Pulsed Drain Current	I_{DM}	320	A
Maximum Power Dissipation	P_D	170	W
Derating factor		1.13	W/℃
Single pulse avalanche energy (Note 5)	E_{AS}	529	mJ
Operating Junction and Storage Temperature Range	T_J,T_{STG}	-55 To 175	℃

Thermal Characteristic

Thermal Resistance,Junction-to-Case (Note 2)	$R_{\theta JC}$	0.88	℃/W

Electrical Characteristics (T_A=25℃unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=250μA	80	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=82V,V_{GS}=0V	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}=±20V,V_{DS}=0V	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=250μA	2		4	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=10V, I_D=20A	-	6		mΩ
Forward Transconductance	g_{FS}	V_{DS}=5V,I_D=20A	-	50	-	S
Dynamic Characteristics (Note4)						
Input Capacitance	C_{lss}	V_{DS}=25V,V_{GS}=0V, F=1.0MHz	-	5633	-	PF
Output Capacitance	C_{oss}		-	268	-	PF
Reverse Transfer Capacitance	C_{rss}		-	226	-	PF
Switching Charact						
Turn-on Delay Time	$t_{d(on)}$	VDD=40V,RL=15Ω RG=2.5Ω,VGS=10V	-	18	-	nS
Turn-on Rise Time	t_r		-	12	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	56	-	nS
Turn-Off Fall Time	t_f		-	15	-	nS
Total Gate Charge	Q_g	V_{DS}=40V,I_D=50A, V_{GS}=10V	-	109.3	-	nC
Gate-Source Charge	Q_{gs}		-	35.1	-	nC
Gate-Drain Charge	Q_{gd}		-	25.8	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V_{SD}	V_{GS}=0V,I_S=95A	-	-	1.2	V
Diode Forward Current (Note 2)	I_S		-	-	95	A
Reverse Recovery Time	t_{rr}	Tj=25℃,I_F=100A di/dt=100A/μs (Note3)	-		37	nS
Reverse Recovery Charge	Qrr		-		58	nC

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production
5. EAS condition：Tj=25℃,V_{DD}=40V,V_{G}=10V,L=0.5mH,Rg=25Ω

Typical Electrical and Thermal Characteristics (Curves



Figure 1 Output Characteristics



Figure 2 Transfer Characteristics



Figure 3 Rdson- Drain Current



Figure 4 Rdson-Junction Temperature



Figure 5 Gate Charge



Figure 6 Source- Drain Diode Forward



Figure 7 Capacitance vs Vds



Figure 9 Power De-rating



Figure 8 Safe Operation Area



Figure 10 I_D Current De-rating



Figure 11 Normalized Maximum Transient Thermal Impedance