Precision pressure regulator
LRP-1/4-10

Part number: 159502





General operating condition

Data sheet

Feature	Value
Actuator lock	Rotary knob with detent
Mounting position	Any
Structural design	Pilot-controlled precision diaphragm regulator
Controller function	Outlet pressure constant With secondary exhausting
Symbol	00991540
Pressure gauge	G1/8 prepared
Operating pressure	0.1 MPa ... 1.2 MPa
Operating pressure	1 bar ... 12 bar
Pressure regulation range	0.1 bar ... 10 bar
Inlet pressure 1	1 bar ... 12 bar
Max. pressure hysteresis	0.02 bar
Standard nominal flow rate	2300 l/min
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4] Inert gas
Information on operating and pilot media	Operation with oil lubrication not possible
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Temperature of medium	-10 °C ... 60 °C
Ambient temperature	-10 °C ... 60 °C
Product weight	310 g
Type of mounting	Front panel mounting Line installation With accessories
Pneumatic connection 1	G1/4
Pneumatic connection 2	G¼
Note on materials	RoHS-compliant
Seals material	NBR
Housing material	Aluminum

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

QS-1/2-16 153151 NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q4-FD-P10 QSF-1/4-8-B QSY-6H-4 QS-1/8-8-I QSML-6 NPQP-T-Q8-E-FD-P10 VABM-B10-25S-G38-6-P3 CRVZS-0.4 NPQP-Y-Q6-E-FD-P10 QS-10H-6 VABM-B10-25S-G38-10 NPQH-T-Q14-E-P10 QSF-3/8-8-B QSLL-G1/2-12 VBQF-U-G14-E 153307 153367 NPQP-D-Q4-S8-FD-P10 NPQP-LQ-R18-Q8-FD-P10 SASC-P4-A-M8-A SGS-M10X1,25 153031 DSBC-80-20-D3-PPSA-N3 QSS-8-F 153269 HGL-1/8-QS-6 NPQP-Y-R12-Q12-FD