
Miniature Relay PT

- **2 pole 12A, 3 pole 10A or 4 pole 6A, 2, 3 or 4 form C (CO) contacts**
- **DC or AC coil**
- **Switching performance up to 3000VA**
- **Relay height 29mm**
- **Mechanical indicator, optional LED and protection diode**
- **Manual test tab, optionally lockable**
- **White marking tabs**



Typical applications
Universal use in control and automation


Approvals


VDE Cert. No. 40009108, UL E214025, Lloyds 00/20059
Technical data of approved types on request

Contact Data	PT2	PT3	PT5
Contact arrangement	2 form C 2 CO	3 form C 3 CO	4 form C 4 CO
Rated voltage		240VAC	
Max. switching voltage	400VAC	400VAC	240VAC
Rated current	12A	10A	6A
Limiting making current, max. 20ms	24A	20A	12A
Limiting breaking current	12A	10A	6A
Limiting short-time current		300A/30ms	
Switching power	3000VA	2500VA	1500VA
Contact material		AgNi90/10, AgNi90/10 gold plated	
Min. recommended contact load		12V at 10mA gold plated: 20mV at 1mA	
Initial voltage drop		30mV at 100mA/6VDC	
Frequency of operation with/without load		360/36000h^{-1}	
Operate time typ., DC coil		15ms	
Release time typ., DC coil, without/with PD		10/18ms	
Bounce time typ., DC coil, form A/form B		6/8ms	

Contact ratings

Type	Contact	Load	Cycles
IEC 61810			
PT 2 DC/AC coil	C (CO)	12A, 250VAC, cosφ=1, 70°C	70x10^3
PT 2 DC/AC coil	A (NO) of C (CO)	9A, 250VAC, cosφ=1, 80°C	150x10^3
PT 2 DC/AC coil	A (NO) of C (CO)	4A, 250VAC, cosφ=1, 80°C	300x10^3
PT 3 DC/AC coil	C (CO)	10A, 250VAC, cosφ=1, 70°C	100x10^3
PT 5 DC/AC coil	C (CO)	6A, 250VAC, cosφ=1, 70°C	100x10^3





Contact Data (continued)

Contact ratings

Type	Contact	Load	Cycles
UL 508			
PT 2	C (CO)	12A, 250VAC, general purpose, 70°C	6.000
PT 2	C (CO)	12A, 250VAC, resistive, 70°C	100x10^3
PT 2	A (NO) of C (CO)	12A, 250VAC, resistive, 70°C	100x10^3
PT 2	A (NO) of C (CO)	12A, 250VAC, resistive, 70°C	100x10^3
PT 3	C (CO)	10A, 250VAC, general purpose, 70°C	6.000
PT 3	C (CO)	10A, 250VAC, resistive, 70°C	100x10^3
PT 3	A (NO) of C (CO)	10A, 250VAC, resistive, 70°C	100x10^3
PT 3	B (NC) of C (CO)	10A, 250VAC, resistive, 70°C	100x10^3
PT 5	C (CO)	6A, 250VAC, general purpose, 70°C	6.000
PT 5	C (CO)	6A, 250VAC, resistive, 70°C	100x10^3
PT 5	A (NO) of C (CO)	6A, 250VAC, resistive, 70°C	100x10^3
PT 5	B (NC) of C (CO)	6A, 250VAC, resistive, 70°C	100x10^3
EN60947-4-1			
PT 2	A (NO) of C (CO)	400VAC, 3.75A, AC3, opposite polarity, 70°C	
PT 2	A (NO) of C (CO)	230VAC, 1.7A, AC5b (400W lamp load), opposite polarity, 70°C	
PT 3	A (NO) of C (CO)	250VAC, 2A, AC3, opposite polarity 70°C	
PT 3	A (NO) of C (CO)	230VAC, 1.7A, AC5b (400W lamp load), opposite polarity, 70°C	
PT 5	A (NO) of C (CO)	250VAC, 3A, AC3, same polarity 70°C	
PT 5	A (NO) of C (CO)	230VAC, 1.7A, AC5b (400W lamp load), same polarity, 70°C	
PT 2	A (NO) of C (CO)	DC coil, AC-15, 250VAC/4A, opposite polarity	6.050
PT 3	A (NO) of C (CO)	DC coil, AC-15, 250VAC/4A, same polarity	6.050
PT 5	A (NO) of C (CO)	DC coil, AC-15, 250VAC/4A, same polarity	6.050
PT 2	A (NO) of C (CO)	AC coil, AC-15, 250VAC/2A, opposite polarity	6.050
PT 3	A (NO) of C (CO)	AC coil, AC-15, 250VAC/2A, same polarity	6.050
PT 5	A (NO) of C (CO)	AC coil, AC-15, 250VAC/2A, same polarity	6.050
PT2/3/5	A (NO) of C (CO)	DC-13, 24VDC/4A	6.050

Mechanical endurance	
DC coil	30x10^6 operations
AC coil	20x10^6 operations

Coil Data

Coil voltage range	6 to 220VDC 6 to 230VAC
Operative range, IEC 61810	
DC coil, AC-coil 50Hz	2
AC coil 60 Hz at 70°C	90..110% of rated voltage
Coil insulation system according UL	class 155 (F)

12-2023, Rev. 1223
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Miniature Relay PT (Continued)

Coil Data (continued)

Coil versions, DC coil, standard

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%[1)2)]	Rated coil power mW
006	6	4.5	0.6	48	750
012	12	9.0	1.2	192	750
024	24	18.0	2.4	777	741
048	48	36.0	4.8	3072	750
060	60	45.0	6	4845[1)]	743
110	110	82.5	11	16133[2)]	750
220	220	165.0	22	64533[2)]	750

Coil versions, DC coil with bipolar LED or LED and protection diode

Coil code bipol. LED	LED+ PD[3)]	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%[1)2)]	Rated coil +LED pwr. mW
L06	LA6	6	4.5	0.6	48	750+3.5
L12	LB2	12	9.0	1.2	192	750+10
L24	LC4	24	18.0	2.4	777	741+18
L48	LE8	48	36.0	4.8	3072	750+38
L60	LG0	60	45.0	6.0	4845[1)]	743+56
M10	MB0	110	82.5	11.0	16133[2)]	750+96.5
N20	NC0	220	165.0	22.0	64533[2)]	750+202.5


1) Coil resistance ±12%, 2) Coil resistance ±15%,
3) Protection diode PD; standard polarity: +A1/-A2
All figures are given for coil without pre-energization, at ambient temperature +23°C

Coil versions, AC coil, 50/60Hz


Coil code STD	LED	Rated voltage VAC	Operate voltage 50/60Hz VAC	Release voltage 50/60Hz VAC	Coil resistance Ω±10%[1)2)]	Rated coil power 50/60Hz VA
506	R06	6	4.8/5.4	1.8	11	1.0/0.85
512	R12	12	9.6/10.8	3.6	48	1.0/0.85
524	R24	24	19.2/21.6	7.2	192	1.0/0.79
548	R48	48	38.4/43.2	14.4	777	1.0/0.87
560	R60	60	48.0/54.0	18.0	1306	1.0/0.87
615	S15	115	92.0/103.5	34.5	4845[1)]	1.0/0.86
730	T30	230	184/207	69.0	19465[2)]	1.0/0.90

1) Coil resistance ±12%, 2) Coil resistance ±15%
All figures are given for coil without pre-energization, at ambient temperature +23°C

Coil operating range DC



Coil operating range AC



Insulation Data	PT2	PT3	PT5
Initial dielectric strength			
between open contacts	1200V$_{rms}$	1200V$_{rms}$	1200V$_{rms}$
between contact and coil	2500V$_{rms}$	2500V$_{rms}$	2500V$_{rms}$
between adjacent contacts	2500V$_{rms}$	2500V$_{rms}$	2000V$_{rms}$
Initial surge withstand voltage between contact and coil	5000V (1.2/50µs)		
Clearance/creepage between contact and coil	≥3/4mm		
Material group of insulation parts	IIIa		
Pollution degree	2		

Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at	www.te.com/customersupport/rohssupportcenter
Ambient temperature	-40 to +70°C
Cold storage, IEC 60068-2-1	-40°C/16h
Dry heat, IEC 60068-2-2	70°C/16h
Category of environmental protection IEC 61810	RTII - flux proof
Vibration resistance (functional), form A (NO)/form B (NC)	7/4g
Shock resistance (functional), form A (NO)/form B (NC)	20/5g
Terminal type	PCB-THT, plug-in quick-connect
Cover retention, pull/push force	100/100N
Weight	30g
Mounting distance, for mounting on PCB	5mm
Resistance to soldering heat THT IEC 60068-2-20	270°C/10s
Packaging unit	10/250pcs.

Accessories

For details see datasheet Accessories Miniature Relay PT

Note: indicated contact ratings and electrical endurance data for direct wiring of relays (according IEC 61810-1); for relays mounted on sockets deratings may apply.

Product Sets

Complete sets consisting of a relay mounted on a socket see Package PT

12-2023, Rev. 1223
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.


Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.


Miniature Relay PT (Continued)

PCB layout / terminal assignment
Bottom view on pins

4 pole




S0354-AA




S0354-AD

3 pole




S0354-AB




S0354-AE

2 pole




S0354-AC




S0354-AF

Circuit

LED




protection diode+LED




Dimensions

Solder- and plug-in terminals (standard version)



PCB version



12-2023, Rev. 1223
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Miniature Relay PT (Continued)

Product code structure — Typical product code: **PT 5 7 0 730**

Type
PT Miniature Relay PT

Contact arrangement
2 2 form C contacts (2 CO contacts)
3 3 form C contacts (3 CO contacts)
5 4 form C contacts (4 CO contacts)

Contact material
7 AgNi 90/10, with test button
2 AgNi 90/10, without test button
8 AgNi 90/10 gold plated, with test button
3 AgNi 90/10 gold plated, without test button

Version
0 Standard: solder/plug-in terminal
1 PCB terminals

Coil
Coil code: please refer to coil versions table

Other types on request

Product code	Cont. Config.	Cont. material	Version	Coil	Coil	Part number
PT270024	2 form C	AgNi 90/10	solder/	DC coil	24VDC	4-1419111-2
PT270524	2 CO contacts	test button	plug-in	AC coil	24VAC	4-1419111-8
PT270615			terminal		115VAC	5-1419111-0
PT270730					230VAC	5-1419111-1
PT270L24				DC coil+LED	24VDC	9-1415001-1
PT270R24				AC coil+LED	24VAC	1415002-1
PT270S15					115VAC	2-1415039-1
PT270T30					230VAC	3-1415002-1
PT271024			PCB terminals	DC coil	24VDC	5-1419111-3
PT271524				AC coil	24VAC	5-1419111-6
PT271615					115VAC	4-1419135-0
PT271730					230VAC	5-1419111-8
PT370024	3 form C	AgNi 90/10	solder/	DC coil	24VDC	6-1419111-1
PT370110	3 CO contacts	test button	plug-in		110VDC	6-1419111-3
PT370524			terminal	AC coil	24VAC	6-1419111-6
PT370615					115VAC	6-1419111-8
PT370730					230VAC	6-1419111-9
PT370L24				DC coil+LED	24VDC	5-1415002-1
PT370R24				AC coil+LED	24VAC	7-1415002-1
PT370S15					115VAC	9-1415039-1
PT370T30					230VAC	9-1415002-1
PT371024			PCB terminals	DC coil	24VDC	7-1419111-1
PT371524				AC coil	24VAC	7-1419111-3
PT371615					115VAC	1393154-8
PT371730					230VAC	7-1419111-5
PT570024	4 form C	AgNi 90/10	solder/	DC coil	24VDC	1-1393154-2
PT570524	4 CO contacts	test button	plug-in	AC coil	24VAC	8-1419111-7
PT570615			terminal		115VAC	9-1419111-0
PT570730					230VAC	9-1419111-1
PT570L24				DC coil+LED	24VDC	6-1415001-1
PT570LC4				DC coil+LED+PD		7-1415541-0
PT570R24				AC coil+LED	24VAC	7-1415001-1
PT570S15					115VAC	7-1415003-1
PT570T30					230VAC	8-1415001-1
PT571024			PCB terminals	DC coil	24VDC	9-1419111-3
PT571524				AC coil	24VAC	9-1419111-6
PT571615					115VAC	1-1393154-5
PT571730					230VAC	9-1419111-8
PT580024		AgNi 90/10	solder/	DC coil	24VDC	1-1393154-7
PT580524		gold plated	plug-in	AC coil	24VAC	2-1393154-1
PT580730		test button	terminal		230VAC	2-1393154-2
PT580L24				DC coil+LED	24VDC	5-1415026-1
PT580R24				AC coil+LED	24VAC	6-1415026-1
PT580T30					230VAC	7-1415026-1
PT581024			PCB terminals	DC coil	24VDC	7-1419135-2
PT581730				AC coil	230VAC	2-1393154-3

12-2023, Rev. 1223
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

2377783-2 917696-1 CPF0402B37K4E1 RH73H2A40MKTN 1-794222-0 175977-2 2-292161-3 2005330-1
1393431-1 1743455-2 3631B101LL TE50BR39J 141991-2 2380312-2 936348-1 U5254-000005-030PA
CRGCQ2010J3K3 SBCHE154R7K SBCHE64R7K 1-962915-1 1969656-1 2310537-1 3-1393225-0
3430B2F51RTDF 650075-000 SMW73R0JT 1903112-2 MPT100C18RF ROX05SJ18R 2834055-1