Mounting kit
SMBR-8-20

Part number: 175095



General operating condition

Data sheet

Feature	Value
Size	20
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Metals with more than 5% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils
Ambient temperature	-20 °C ... 70 °C
Profile material	Wrought aluminum alloy
Note on materials	RoHS-compliant
Retaining bracket material	POM

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

DFM-63-100-P-A-KF DSBC-32-40-D3-PPVA-N3 DSNU-12-60-P-A QSLV-G1/4-6 N-1/8-P-6 CRVZS-0.4 DSBC-80-250-D3-PPSA-N3 NPQP-LQ-R18-Q8-FD-P10 QSLL-1/4-4 QSML-3 SPTE-V1R-Q3-V-2.5K DSBC-32-50-D3-PPVA-N3 DSBC-50-20-D3-PPSA-N3 DSBC-63-320-D3-PPVA-N3 DSBC-80-320-D3-PPVA-N3 MSFW-110-50/60-DS QS-1/2-16 VBQF-U-G14-E NPQP-L-Q10-E-FD-P10 NPQP-Y-Q6-E-FD-P10 NPQH-T-G38-Q8-P10 NPQP-D-Q4-S8-FD-P10 NPQP-LQ-R18-Q4-FD-P10 PUN-H-4X0,75-TBL QSML-6 SNC-63 NPQP-Y-R12-Q12-FD QH-1 1/2 QSS-8-F VABM-L1-18W-G38-8-G