
Molded Power Inductor
CSEB0440H Series



Construction Wire

Outline:

- Magnetic shielded structure:excellent resistance to electro Magnetic interference (EMI)
- A composite structure,ultra low buzz noise
- Low loss,high efficiency,wide application frequency
- Lightweight design,save space,suitable for high density SMT

Features:

- Core material: Alloy powder
- Environmental: RoHS, Reach compliant ,Halogen free
- Weight:0.40g
- Moisture Sensitivity:Level (MSL) 1 (unlimited floor life at 5 ~ 40℃, RH≤ 70% relative humidity).
- Operating temperature range: -40℃ ~ +125℃ (including coil's self temperature rise)
- Storage temperature range: -40℃～+125℃

Application:

- PDA/notebook/desktop/server applications
- DC /DC converters for entertainment/navigations systems
- Noise suppression for motors:windshield wipers/power seats/Power Mirrors/heating and ventilation blower/ HID lighting

1 Electrical Characteristics

Part No.	Inductance (μH)※1 ±20%	D.C.R. (mΩ) Typical	D.C.R. (mΩ) Max.	Isat (A)※2 Max.	Irms (A) ※3 Max.
CSEB0440H-3R3M	3.30	21.0	25.0	5.20	6.60
CSEB0440H-4R7M	4.70	29.0	35.0	4.70	6.00
CSEB0440H-5R6M	5.60	38.0	44.5	4.30	5.60
CSEB0440H-6R8M	6.80	45.0	55.0	3.60	5.00


All data is tested on 25℃ ambient temperature

1.Inductance measure condition at 100kHz,0.1V


2.Isat:the actual value of DC current when the inductance decrease 30% of its initial value

3.Irms:the actual value of DC current when the temperature rise is ΔT40℃(Ta=25℃)

2 Product Dimensions (mm)



3 How to Order:




CODACA ELECTRONIC CO., LTD


TEL: +86 755 89585372 FAX: +86 755 89585280
http://www.codaca.com E-mail: info@codaca.com


This product is not authorized for use in any application related to safety.
Specification subject to change without notice. Please check web site for latest information.


Revised: 07/14/2020

4 Saturation Current vs Temperature Rise Current Curve











5 L vs Frequency


CSEB0440H-3R3M




CSEB0440H-4R7M



CSEB0440H-5R6M




CSEB0440H-6R8M




6 Impedance vs Frequency


CSEB0440H-3R3M




CSEB0440H-4R7M



CSEB0440H-5R6M




CSEB0440H-6R8M




7 Packing Specification


7.1 Carrier Tape Dimensions (mm)



※ Packing is referred to the international standard IEC 60286-3.

7.2 Reel Dimensions (mm)






7.3 Carton Dimensions and Packing Quantity

■ Inner Carton : 340×340×95mm ■ Outer Carton : 360×360×370mm

Product Series	Quantity / Reel	Inner Carton Quantity	Outer Carton Quantity
CSEB0440H	1500pcs	(1500×4) = 6000pcs	(6000×3) = 18000pcs

8 Soldering Specification

8.1 Reflow Profile for SMT Components



8.2 Classification of Peak Package Body Temperature (T_P)

	Package Thickness	Package Volume		
		<350 mm^3	350～2000 mm^3	>2000 mm^3
PB-Free Assembly	<1.6mm	260℃	260℃	260℃
	1.6～2.5mm	260℃	250℃	245℃
	≥2.5mm	250℃	245℃	245℃

※ Reflow is referred to standard IPC/JEDEC J-STD-020E.

9 Notice of Use

9.1 Special remind:Circuit design, component placement, PCB size and thickness, cooling system and etc. all will affect the product temperature. Please verify the product temperature in the final application.

9.2 Product in packing storage condition:temperature 5～40℃, RH≤ 70%.
If taking out for use, the remaining products should be sealed in plastic bags and preserved in accordance With the above conditions, to avoid oxidation of terminals (electrodes), affecting soldering status.

9.3 A storage of Codaca Electronic products for longer than 12 months is not recommended, Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.

9.4 Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust or corrosion.

9.5 Always handle products with care.

9.6 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering. Always ensure optimum conditions for soldering.

9.7 When this product will be used on a similar or new project to the original one, sometimes it might be unable to satisfy the specifications due to different condition of usage.

9.8 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., or use in abnormal conditions protective devices or protection circuit in the end product.

9.9 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.

9.10 If using in potting compound, the magnet wire coating might be damaged, please consult with us.

9.11 Refrain from rinsing product. If necessary, please consult with us.

*9.12 Codaca Electronic products without "V" prefix are qualified for industrial product requirement , and with "V" prefix are qualified for AEC-Q200, but it doesn't mean that Codaca Electronic products can absolutely meet specific industry norms and quality test standards in automotive electronics or more strict application fields . Codaca Electronic will be exempted from being responsible for the consequences of using Codaca products in automotive electronic or higher application field related to safety when without being aware of it.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

CODACA:

CSAB1040A-3R3M CSBL1809-1R3M CSBL1809-470M CSHB0540R-4R7M VSHB0754T-4R7MC
CPCE2624A-270MC CSAB1050A-100M CSBL1265-150M CSEB0440H-4R7M CSHB0430R-2R2M
CPEA2622L-2R2MC CPEA2626L-150MC CPEX2722-120MC CSEB0420H-R22M CSEB0430H-1R2M
CSEB0440H-3R3M SPRH1210-270M VSHB0540-2R2MC VSHB0421-1R0MC CPRX3231L-180MC
CSBX1265-180M CSBX2212-150M SPRH125-220M VSEB0630H-1R2MC VSHB1054T-680MC
CSAB0530-3R3M CSAB0750-470M VSHB0754T-5R6MC CSAB0530-220M CSAB1040A-1R2M