# MC10H174

# Dual 4 to 1 Multiplexer

**ON Semiconductor®**

**http://onsemi.com**


### Description


The MC10H174 is a Dual 4−to−1 Multiplexer. This device is a functional/ pinout duplication of the standard MECL 10K™ part, with 100% improvement in propagation delay and no increase in power supply current.

### Features


- Propagation Delay, 1.5 ns Typical
- Power Dissipation, 305 mW Typical
- Improved Noise Margin 150 mV (over operating voltage and temperature range)
- Voltage Compensated
- MECL 10K Compatible
- Pb−Free Packages are Available*

**MARKING DIAGRAMS***






**CDIP−16**
**L SUFFIX**
**CASE 620A**










**PDIP−16**
**P SUFFIX**
**CASE 648**






**SOEIAJ−16**
**CASE 966**




**PLLC−20**
**FN SUFFIX**
**CASE 775**

| | |
|---|---|
| A | = Assembly Location |
| WL, L | = Wafer Lot |
| YY, Y | = Year |
| WW, W | = Work Week |
| G | = Pb−Free Package |

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


*For additional marking information, refer to Application Note AND8002/D.

### ORDERING INFORMATION


See detailed ordering and shipping information in the package dimensions section on page 3 of this data sheet.

© Semiconductor Components Industries, LLC, 2006

## LOGIC DIAGRAM




## DIP PIN ASSIGNMENT




Pin assignment is for Dual−in−Line Package.
For PLCC pin assignment, see the Pin Conversion Tables on page 18 of the ON Semiconductor MECL Data Book (DL122/D).

## TRUTH TABLE

| $\overline{\text{ENABLE}}$ | ADDRESS INPUTS | | OUTPUTS | |
|---|---|---|---|---|
| $\overline{E}$ | B | A | Z | W |
| H | X | X | L | L |
| L | L | L | X0 | Y0 |
| L | L | H | X1 | Y1 |
| L | H | L | X2 | Y2 |
| L | H | H | X3 | Y3 |

**Table 1. MAXIMUM RATINGS**

| Symbol | Characteristic | Rating | Unit |
|---|---|---|---|
| $V_{EE}$ | Power Supply ($V_{CC}$ = 0) | −8.0 to 0 | Vdc |
| $V_I$ | Input Voltage ($V_{CC}$ = 0) | 0 to $V_{EE}$ | Vdc |
| $I_{out}$ | Output Current − Continuous<br>− Surge | 50<br>100 | mA |
| $T_A$ | Operating Temperature Range | 0 to +75 | °C |
| $T_{stg}$ | Storage Temperature Range − Plastic<br>− Ceramic | −55 to +150<br>−55 to +165 | °C<br>°C |

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

**Table 2. ELECTRICAL CHARACTERISTICS** ($V_{EE}$ = −5.2 V ±5%) (Note 1)

| Symbol | Characteristic | 0° | | 25° | | 75° | | Unit |
|---|---|---|---|---|---|---|---|---|
| | | Min | Max | Min | Max | Min | Max | |
| $I_E$ | Power Supply Current | – | 80 | – | 73 | – | 80 | mA |
| $I_{inH}$ | Input Current High | | | | | | | μAdc |
| | Pins 3–7 & 9–13 | – | 475 | – | 300 | – | 300 | |
| | Pin 14 | – | 670 | – | 420 | – | 420 | |
| $I_{inL}$ | Input Current Low | 0.5 | – | 0.5 | – | 0.3 | – | μA |
| $V_{OH}$ | High Output Voltage | −1.02 | −0.84 | −0.98 | −0.81 | −0.92 | −0.735 | Vdc |
| $V_{OL}$ | Low Output Voltage | −1.95 | −1.63 | −1.95 | −1.63 | −1.95 | −1.60 | Vdc |
| $V_{IH}$ | High Input Voltage | −1.17 | −0.84 | −1.13 | −0.81 | −1.07 | −0.735 | Vdc |
| $V_{IL}$ | Low Input Voltage | −1.95 | −1.48 | −1.95 | −1.48 | −1.95 | −1.45 | Vdc |

1. Each MECL 10H™ series circuit has been designed to meet the dc specifications shown in the test table, after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse air flow greater than 500 linear fpm is maintained. Outputs are terminated through a 50 Ω resistor to −2.0 V.

**Table 3. AC PARAMETERS**

| Symbol | Characteristic | 0° | | 25° | | 75° | | Unit |
|---|---|---|---|---|---|---|---|---|
| | | Min | Max | Min | Max | Min | Max | |
| $t_{pd}$ | Propagation Delay | | | | | | | ns |
| | Data | 0.7 | 2.4 | 0.8 | 2.5 | 0.9 | 2.6 | |
| | Select (A, B) | 1.0 | 2.8 | 1.1 | 2.9 | 1.2 | 3.2 | |
| | Enable | 0.4 | 1.45 | 0.4 | 1.5 | 0.5 | 1.7 | |
| $t_r$ | Rise Time | 0.5 | 1.5 | 0.5 | 1.6 | 0.5 | 1.7 | ns |
| $t_f$ | Fall Time | 0.5 | 1.5 | 0.5 | 1.6 | 0.5 | 1.7 | ns |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfpm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.


## ORDERING INFORMATION


| Device | Package | Shipping† |
|---|---|---|
| MC10H174FN | PLLC−20 | 46 Units / Rail |
| MC10H174FNG | PLLC−20 (Pb−Free) | 46 Units / Rail |
| MC10H174FNR2 | PLLC−20 | 500 / Tape & Reel |
| MC10H174FNR2G | PLLC−20 (Pb−Free) | 500 / Tape & Reel |
| MC10H174L | CDIP−16 | 25 Unit / Rail |
| MC10H174M | SOEIAJ−16 | 50 Unit / Rail |
| MC10H174MG | SOEIAJ−16 (Pb−Free) | 50 Unit / Rail |
| MC10H174MEL | SOEIAJ−16 | 2000 / Tape & Reel |
| MC10H174MELG | SOEIAJ−16 (Pb−Free) | 2000 / Tape & Reel |
| MC10H174P | PDIP−16 | 25 Unit / Rail |
| MC10H174PG | PDIP−16 (Pb−Free) | 25 Unit / Rail |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

## PACKAGE DIMENSIONS

**20 LEAD PLLC**
CASE 775−02
ISSUE E








NOTES:
1. DIMENSIONS AND TOLERANCING PER ANSI Y14.5M, 1982.
2. DIMENSIONS IN INCHES.
3. DATUMS –L–, –M–, AND –N– DETERMINED WHERE TOP OF LEAD SHOULDER EXITS PLASTIC BODY AT MOLD PARTING LINE.
4. DIMENSION G1, TRUE POSITION TO BE MEASURED AT DATUM –T–, SEATING PLANE.
5. DIMENSIONS R AND U DO NOT INCLUDE MOLD FLASH. ALLOWABLE MOLD FLASH IS 0.010 (0.250) PER SIDE.
6. DIMENSIONS IN THE PACKAGE TOP MAY BE SMALLER THAN THE PACKAGE BOTTOM BY UP TO 0.012 (0.300). DIMENSIONS R AND U ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF THE PLASTIC BODY.
7. DIMENSION H DOES NOT INCLUDE DAMBAR PROTRUSION OR INTRUSION. THE DAMBAR PROTRUSION(S) SHALL NOT CAUSE THE H DIMENSION TO BE GREATER THAN 0.037 (0.940). THE DAMBAR INTRUSION(S) SHALL NOT CAUSE THE H DIMENSION TO BE SMALLER THAN 0.025 (0.635).

| | INCHES | | MILLIMETERS | |
|---|---|---|---|---|
| DIM | MIN | MAX | MIN | MAX |
| A | 0.385 | 0.395 | 9.78 | 10.03 |
| B | 0.385 | 0.395 | 9.78 | 10.03 |
| C | 0.165 | 0.180 | 4.20 | 4.57 |
| E | 0.090 | 0.110 | 2.29 | 2.79 |
| F | 0.013 | 0.019 | 0.33 | 0.48 |
| G | 0.050 BSC | | 1.27 BSC | |
| H | 0.026 | 0.032 | 0.66 | 0.81 |
| J | 0.020 | −−− | 0.51 | −−− |
| K | 0.025 | −−− | 0.64 | −−− |
| R | 0.350 | 0.356 | 8.89 | 9.04 |
| U | 0.350 | 0.356 | 8.89 | 9.04 |
| V | 0.042 | 0.048 | 1.07 | 1.21 |
| W | 0.042 | 0.048 | 1.07 | 1.21 |
| X | 0.042 | 0.056 | 1.07 | 1.42 |
| Y | −−− | 0.020 | −−− | 0.50 |
| Z | 2 ° | 10 ° | 2 ° | 10 ° |
| G1 | 0.310 | 0.330 | 7.88 | 8.38 |
| K1 | 0.040 | −−− | 1.02 | −−− |

## PACKAGE DIMENSIONS


**SOEIAJ−16**
CASE 966−01
ISSUE A




NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS AND ARE MEASURED AT THE PARTING LINE. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
5. THE LEAD WIDTH DIMENSION (b) DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE LEAD WIDTH DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT. MINIMUM SPACE BETWEEN PROTRUSIONS AND ADJACENT LEAD TO BE 0.46 ( 0.018).

| | MILLIMETERS | | INCHES | |
|---|---|---|---|---|
| DIM | MIN | MAX | MIN | MAX |
| A | --- | 2.05 | --- | 0.081 |
| $A_1$ | 0.05 | 0.20 | 0.002 | 0.008 |
| b | 0.35 | 0.50 | 0.014 | 0.020 |
| c | 0.10 | 0.20 | 0.007 | 0.011 |
| D | 9.90 | 10.50 | 0.390 | 0.413 |
| E | 5.10 | 5.45 | 0.201 | 0.215 |
| e | 1.27 BSC | | 0.050 BSC | |
| $H_E$ | 7.40 | 8.20 | 0.291 | 0.323 |
| L | 0.50 | 0.85 | 0.020 | 0.033 |
| $L_E$ | 1.10 | 1.50 | 0.043 | 0.059 |
| M | 0 ° | 10 ° | 0 ° | 10 ° |
| $Q_1$ | 0.70 | 0.90 | 0.028 | 0.035 |
| Z | --- | 0.78 | --- | 0.031 |

**CDIP−16**
**L SUFFIX**
CERAMIC DIP PACKAGE
CASE 620A−01
ISSUE O





NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.
4. DIMENSION F MAY NARROW TO 0.76 (0.030) WHERE THE LEAD ENTERS THE CERAMIC BODY.
5 THIS DRAWING REPLACES OBSOLETE CASE OUTLINE 620−10.

| | INCHES | | MILLIMETERS | |
|---|---|---|---|---|
| DIM | MIN | MAX | MIN | MAX |
| A | 0.750 | 0.785 | 19.05 | 19.93 |
| B | 0.240 | 0.295 | 6.10 | 7.49 |
| C | --- | 0.200 | --- | 5.08 |
| D | 0.015 | 0.020 | 0.39 | 0.50 |
| E | 0.050 BSC | | 1.27 BSC | |
| F | 0.055 | 0.065 | 1.40 | 1.65 |
| G | 0.100 BSC | | 2.54 BSC | |
| H | 0.008 | 0.015 | 0.21 | 0.38 |
| K | 0.125 | 0.170 | 3.18 | 4.31 |
| L | 0.300 BSC | | 7.62 BSC | |
| M | 0 ° | 15 ° | 0 ° | 15 ° |
| N | 0.020 | 0.040 | 0.51 | 1.01 |

## PACKAGE DIMENSIONS

**PDIP−16**
**P SUFFIX**
PLASTIC DIP PACKAGE
CASE 648−08
ISSUE R




NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.
5. ROUNDED CORNERS OPTIONAL.

| | INCHES | | MILLIMETERS | |
|---|---|---|---|---|
| DIM | MIN | MAX | MIN | MAX |
| A | 0.740 | 0.770 | 18.80 | 19.55 |
| B | 0.250 | 0.270 | 6.35 | 6.85 |
| C | 0.145 | 0.175 | 3.69 | 4.44 |
| D | 0.015 | 0.021 | 0.39 | 0.53 |
| F | 0.040 | 0.70 | 1.02 | 1.77 |
| G | 0.100 BSC | | 2.54 BSC | |
| H | 0.050 BSC | | 1.27 BSC | |
| J | 0.008 | 0.015 | 0.21 | 0.38 |
| K | 0.110 | 0.130 | 2.80 | 3.30 |
| L | 0.295 | 0.305 | 7.50 | 7.74 |
| M | 0 ° | 10 ° | 0 ° | 10 ° |
| S | 0.020 | 0.040 | 0.51 | 1.01 |

MECL 10H and MECL 10K are trademarks of Motorola, Inc.

**ON Semiconductor** and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT**:
Literature Distribution Center for ON Semiconductor
P.O. Box 61312, Phoenix, Arizona 85082−1312 USA
**Phone**: 480−829−7710 or 800−344−3860 Toll Free USA/Canada
**Fax**: 480−829−7709 or 800−344−3867 Toll Free USA/Canada
**Email**: orderlit@onsemi.com

**N. American Technical Support**: 800−282−9855 Toll Free USA/Canada

**Japan**: ON Semiconductor, Japan Customer Focus Center
2−9−1 Kamimeguro, Meguro−ku, Tokyo, Japan 153−0051
**Phone**: 81−3−5773−3850

**ON Semiconductor Website**: http://onsemi.com

**Order Literature**: http://www.onsemi.com/litorder

For additional information, please contact your local Sales Representative.

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## ON Semiconductor:

FDMS7608S LA4440J-E MC74LCX02DTR2G SZ1SMA5913BT3G LB1861M-TLM-H LV8014T-TLM-E
NCV5501DT33RKG TLV431CSN1T1G MC33077DR2G MOC212R2M NCP1397BDR2G CS8182YDPSR5G
FOD2741AV NC7WV07P6X NCS20081MUTAG 1SMA5938BT3G MMBTH81 NCP1342ENDCEAD1R2G
NCP1566MNTXG LM393NG MC34152DR2G MC74ACT541DWG NTBG060N090SC1 KSA1156OSTSTU
NB3N853531EDTG UC2845BD1R2G CNY17-3V-M FDMA7672 LM385BD-2.5R2G NCP114AMX250TCG