
Rotary actuator
DRVS-12-270-P

Part number: 1845712





General operating condition

Data sheet

Feature	Value
Size	12
Cushioning angle	0.5 deg
Swivel angle	0 deg ... 270 deg
Permissible stop radius	15 mm
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Mode of operation	Double-acting
Structural design	Rotary vane
Position sensing	For proximity sensor
Symbol	00991265
Variants	Spigot shaft
Operating pressure	0.25 MPa ... 0.8 MPa
Operating pressure	2.5 bar ... 8 bar
Max. swivel frequency at 6 bar	2 Hz
Repetition accuracy	1 deg
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Cleanroom class	Class 6 according to ISO 14644-1
Ambient temperature	0 °C ... 60 °C
Max. stop force	90 N
Max. axial force	20 N
Max. radial force	25 N
Theoretical torque at 6 bar	1 Nm
Permissible mass moment of inertia	0.005 kgm²
Product weight	150 g
Type of mounting	With internal thread
Pneumatic connection	M5
Note on materials	RoHS-compliant
Drive shaft material	High-alloy stainless steel
Seals material	TPE-U(PU)
Housing material	Die cast aluminum, painted

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

153151 NPQH-T-Q14-E-P10 NPQP-LQ-R18-Q8-FD-P10 QSML-6 QS-1/2-16 QS-10H-6 VABM-B10-25S-G38-10 153269 153307 CRVZS-0.4 HGL-1/8-QS-6 NPQP-Y-R12-Q12-FD 153031 QSF-3/8-8-B QSLL-G1/2-12 NPQP-T-Q8-E-FD-P10 QS-1/8-8-I QSY-6H-4 SASC-P4-A-M8-A VBQF-U-G14-E NPQP-D-Q4-S8-FD-P10 NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q4-FD-P10 QSS-8-F SGS-M10X1,25 QSF-1/4-8-B 153367 DSBC-80-20-D3-PPSA-N3 NPQP-Y-Q6-E-FD-P10 VABM-B10-25S-G38-6-P3