
ESD Bench Matting – Smooth Finish – Grey


RoHS Compliant

Features:
Anti-static matting should be laid out in the workshops or advanced laboratories for microelectronic industries such as electronic semi-conduct devices, electronic computers, electronic communication equipment and integrated circuits etc.


- Great value ESD Bench Matting
- Made from anti-static (conductive) and static-dissipative materials with synthetic rubber
- 2mm thick double-layer structure
- Surface layer is a 0.5mm thick static-dissipative layer
- Bottom layer is a 1.5mm conductive layer
- Asian origin
- Green and Blue colours also available



Construction:



Colours / Finish:



Grey

Product Code:	Description:	Mat Size:	Additional Notes:
1687901	ESD Bench Matting - Smooth Finish with 1 stud to long side	1200 x 1500mm	Grey (Ref: 082-0034F2)

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2011.

ESD Bench Matting – Smooth Finish – Grey

RoHS Compliant

GROUNDING:
Sufficient ground cords should be used to reliably meet EN 61340-5-1 Table 3 less than 1 x 10^9 ohms for working surfaces. Industry recommendation is that continuous runs of ESD matting should be grounded at 10ft intervals to allow proper charge decay rates. Each individual ESD mat should be grounded with ground snaps located no further than five feet from either end.

CLEANING:
Please note that contact between the matting surface and any acid or alkali solvent is strictly prohibited (such as Benzene, Alcohol etc), this will result in the antistatic performance wearing away. If cleaning is required, the matting may be wiped with a cloth coated in a neutral solution (such as water).

GUIDANCE ON USE:
Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Matting should always be trimmed with a sharp knife or razor blade.

CUTTING TOLERANCES:
Width $\pm$ 6mm
Length $\pm$ 6mm every linear foot of running material

RoHS COMPLIANCE:
None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1.

Test Results:

	Test Method:	**Unit:**	**Value:**
Surface Resistance / R_{TG}	SJ/T10694-2004	Ω	$1x10^6 \leq R \leq 1x10^9$
Bottom Resistance / R_{TT}	SJ/T10694-2004	Ω	$1x10^3 \leq R \leq 1x10^6$
Volume Resistance	GB/T14437-97	Ω	$1x10^5 \leq R \leq 1x10^8$
Thickness	YY-1001	mm	Permissible Tolerance +0.1
Temperature Resistance	YY-1001	°C	180 (Instantaneous Temp)
Temperature	N/A	°C	20-26
Relative Humidity	N/A	%	40-65

R_{TG} is the resistance from one point on the mat's surface to the mat's ground point, and is the fundamental electrical test for a mat. A proper R_{TG} insures that a mat can conduct charge from a point on the surface to the mat ground point. The guideline in ESD STM-4.1 for R_{TG} is $1x10^6$ to $1x10^9$ ohms. ANSI/ESD S-20.20 has an upper limit of $<1 x10^9$ ohms.

R_{TT} is the resistance from one point on the mat's surface to another point. A proper R_{TT} insures the consistency of the mat's resistance properties. The ESD STM-4.1 guideline for R_{TT} is $>1x10^6$ ohms.

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2011.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

multicomp:

CF06332T/4/10 MCSDRH73B-681MHF MC0603N100J201CT MCMR50V335M4X7 MCMET 800MA 250V MCSR08X3300FTL MC34747 MC36427 MCAL0410A1-471KU MCMF0W4FF8202A50 MCMR08X2000FTL MP005415 CFS-TF-1818 CMS-DF-1825 MC34589 MP006964 2213R-24G MC-SVT1-S06-G MC0402WGF499JTCE MCMR06X1004FTL MCSDC0603-560KU MUR1540 SPC19989 MC0603B393K500CT MC0603N100F500CT MCLPR50V478M30X25 MCWR08X39R0FTL MCWF12R7150BTL MP006937 SMAJ160A-13-F