

Rotary actuator
DSM-16-270-P-A-B

Part number: 547574





General operating condition

Data sheet

Feature	Value
Size	16
Cushioning angle	1.4 deg
Adjustment range of swivel angle	0 deg ... 270 deg
Swivel angle	0 deg ... 270 deg
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Precision adjustment	-6 deg
Mode of operation	Double-acting
Structural design	Rotary vane
Position sensing	For proximity sensor
Symbol	00991265
Operating pressure	0.18 MPa ... 1 MPa
Operating pressure	1.8 bar ... 10 bar
Max. swivel frequency at 6 bar	2 Hz
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Corrosion resistance class (CRC)	0 - No corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Cleanroom class	Class 6 according to ISO 14644-1
Ambient temperature	-10 °C ... 60 °C
Max. axial force	30 N
Max. radial force	75 N
Theoretical torque at 6 bar	2.5 Nm
Permissible mass moment of inertia	0.01 kgm²
Product weight	470 g
Type of mounting	With internal thread
Pneumatic connection	M5
Note on materials	RoHS-compliant
Drive shaft material	Steel Nickel-plated
Seals material	TPE-U(PU)
Housing material	Wrought aluminum alloy

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

QS-10H-6 QSML-6 CRVZS-0.4 QSY-6H-4 153269 NPQH-T-Q14-E-P10 NPQP-L-Q10-E-FD-P10 NPQP-T-Q8-E-FD-P10 QSLL-G1/2-12 153307 QSF-1/4-8-B QSS-8-F VABM-B10-25S-G38-6-P3 NPQP-Y-R12-Q12-FD QSF-3/8-8-B SGS-M10X1,25 153367 SASC-P4-A-M8-A VABM-B10-25S-G38-10 VBQF-U-G14-E 153151 DSBC-80-20-D3-PPSA-N3 NPQP-D-Q4-S8-FD-P10 QS-1/2-16 153031 HGL-1/8-QS-6 NPQP-LQ-R18-Q4-FD-P10 NPQP-LQ-R18-Q8-FD-P10 NPQP-Y-Q6-E-FD-P10 QS-1/8-8-I