ISL95908

Integrated Power Management IC for IMVP8 Platforms

FN8730
Rev.1.00
Mar 23, 2017

The ISL95908 is a Power Management Integrated Circuit (PMIC) for ultrabook, notebook, and tablet computers powered by 2-cell Li-ion batteries. It integrates control, MOSFET drivers, power MOSFETs, fault protection, and fault monitoring functions for eight highly efficient synchronous buck regulators and VTT LDO. It is offered in a thermally efficient 5.5mmx5.5mm, 121-bump, 0.5mm pitch WLCSP package.

The PMIC regulators convert system voltage from the battery or adapter into all platform voltages needed for a typical computer system including 5V and 3.3V system regulators, 1.8V/2.5V, 1V, 0.975V, 0.9V for controller-hub, peripheral and core voltages, as well as programmable VDDQ and VTT regulators for DDR3/3U/3L, LPDDR3, and DDR4 voltages. The switching regulators operate at 1MHz and are based on Intersil's proprietary R4™ Technology, which provides high light-load efficiency, fast transient response, seamless DCM/CCM transitions, and requires no external compensation.

The PMIC provides overcurrent, overvoltage and over-temperature fault protections, and undervoltage and over-temperature warnings. A temperature alert signal indicates the PMIC is operating at an elevated temperature and ALERT indicates if any other fault or warning has occurred. The PMIC also offers significant I^2C capability and can be configured to provide eight GPIO pins for additional system functionality and each regulator has an independent power-good indicator.

Related Literature

- For a full list of related documents, visit our website
  - ISL95908 product page
- UG027, "ISL95908EVAL1Z Evaluation Board User Guide"

Features

- Highly integrated power management IC
- Efficient 1MHz integrated FET switching regulators
- Internal compensation, no external compensation
- Computer system platform voltage regulators 5V, 3.3V, 1.8V/2.5V, 1V, 0.975V, 0.9V
- Programmable VR3 and VTT regulators for memory (DDR3/L/U, LPDDR3, and DDR4)
- Extensive fault protection
  - Overcurrent protection
  - Over-temperature protection
  - Overvoltage and undervoltage protection
  - Temperature alert signal
- Independent power-good indicator for each regulator
- Independent enable signals for each regulator for maximum sequencing flexibility
- Low power consumption mode for connected standby
- I^2C bus allows system fault monitoring, enable control, and configurable GPIO programming
- Output voltage offset programming through I^2C
- Configuration pin provides additional system programming options

Applications

- Ultrabook, notebook, and tablet computers




FIGURE 1. COMPUTER SYSTEM POWER MANAGEMENT SOLUTION

Downloaded from Arrow.com.

© Copyright Intersil Americas LLC 2015-2017. All Rights Reserved.
All trademarks and registered trademarks are the property of their respective owners.

For additional products, see www.intersil.com/en/products.html

Intersil products are manufactured, assembled and tested utilizing ISO9001 quality systems as noted in the quality certifications found at www.intersil.com/en/support/qualandreliability.html

Intersil products are sold by description only. Intersil may modify the circuit design and/or specifications of products at any time without notice, provided that such modification does not, in Intersil's sole judgment, affect the form, fit or function of the product. Accordingly, the reader is cautioned to verify that datasheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com

Downloaded from Arrow.com.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Renesas Electronics:

M62354AGP#DF5J XLL726125.000000I RV1S9261ACCSP-10YV#SC0 X5043S8IZ-2.7AT1 PS2561DL-1Y-F3-A R5F56609BDFP#30 XLH536010.000000I XLL726200.000000I HIN211ECAZ-T R5F52316CDFP#30 ZMOD4450AI4V DA14697-00000HR2 ISL81487LIPZ R5F566TAADFM#30 R9A02G0214CNK#UA0 8P34S1102NLGI8 IPS2200STKIT ISL96017UIRT8Z R5F100GCGFB#10 R5F10BGGLNA#U5 R5F11TLGDFB#35 R5F51135ADFM#3A RTK9744C22S01000BE 5V41234NLGI M38D59GCHP#U0 RTKA211230DE0020BU EL7457CUZ R5F72167ADFP#V1 RTK0EG0003S02001BJ TP65H150BG4JSG-TR