Part Number : 1724660200
Product Description : iPass+ zHD Vertical Internal Connector Assembly, 1x2, Surface Mount, 0.76µm Gold (Au) Plating
Series Number : 172466
Status : Active
Product Category : High-Speed I/O Connectors



Documents & Resources

Drawings

Drawing 1724660200_sd.pdf
Packaging Design Drawing PK-172466-9001-000.pdf

3D Models and Design Files

3D Model 1724660200_stp.zip
Electrical Model Document EE-172466_0100-001.pdf
S-Parameter Model SP-172466-0100-001.zip

Specifications

Application Specification AS-172466-002-001.pdf
Product Specification PS-172466-001-001.pdf
Test Summary TS-172466-0100-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	High-Speed I/O Connectors
Series	172466
Description	iPass+ zHD Vertical Internal Connector Assembly, 1x2, Surface Mount, 0.76µm Gold (Au) Plating
Application	Wire-to-Board
Component Type	Internal Receptacle
Product Family	iPass+ HD Interconnect System
Product Name	iPass+,zHD
Type	Pluggable
UPC	889056428552

Agency

CSA	LR19880
UL	E107635

Electrical

Current - Maximum per Contact	1.0A
Voltage - Maximum	30V AC (RMS) / 42V DC

Physical

Circuits (Loaded)	72
Circuits (maximum)	72
Color - Resin	Black
Durability (mating cycles max)	50

Flammability	94V-0
Gender	Receptacle
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	4.559/g
Number of Rows	4
Orientation	Vertical
Packaging Type	Embossed Tape on Reel
Panel Mount	No
PCB Locator	Yes
PCB Retention	Yes
Pitch - Mating Interface	0.75mm
Plating min - Mating	0.760µm
Plating min - Termination	0.760µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	2
Temperature Range - Operating	-40° to +80°C
Termination Interface Style	Surface Mount

Mates With / Use With

Mates with Part(s)

Description	Part Number
Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies	100171
Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies	100172
Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies	100189
Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies	100190
Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies	100219

Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies	100220
Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies	100221
Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies	100222
Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies	100223
Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies	100224
Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies	100225
Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies	100226

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

molex:

464373005 194270031 194290039 348268126 502380-0800 34708-2028 459850483 528061110
197134001 347928042 355240920 357470310 502584-0870 528523070 503988100 0477256010
197054301 349672001 351820290 502584-1060 502585-0370 347072012 347910140 528520870
0194360214 0464363133 348242245 5023860371 0351510214 194290026