Ball valve
VZBE-11/2-T-63-T-2-F0507-V15V15

Part number: 4809121





General operating condition

Data sheet

Feature	Value
Structural design	2-way ball valve
Actuation type	Mechanical
Sealing principle	Soft
Mounting position	Any
Type of mounting	Line installation
Fitting connection	1 1/2 NPT
Switching position indication	Slot direction = flow direction
Flange hole pattern	F0507
Inside diameter	38 mm
Nominal width DN	40
Valve function	2/2
Flow direction	Reversible

Feature	Value
Nominal pressure of fitting PN	63
Breakaway torque at differential pressure, nominal pressure, fitting PN	30 Nm
Based on norm	ASME B1.20.1 ISO 5211
Symbol	00991458
Medium	Vapor Compressed air as per ISO 8573-1:2010 [-:-:-] Inert gas Water Neutral liquids
Temperature of medium	-20 °C ... 200 °C
Flow rate Kv	247 m³/h
Note on materials	RoHS-compliant
LABS (PWIS) conformity	VDMA24364 zone III
Housing material	Cast stainless steel
Material number of housing	1.4408
Seat seal material	PTFE
Seals material	FPM PTFE
Ball material	Cast stainless steel
Material number for ball	1.4408
Shaft material	High-alloy stainless steel
Material number for shaft	1.4401
Product weight	2420 g
Certification	CRN
CE marking (see declaration of conformity)	as per EU pressure equipment directive
Explosion prevention and protection	Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX)
Corrosion resistance class (CRC)	4 - Particularly high corrosion stress

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

CRVZS-0.4 HGL-1/8-QS-6 QSML-6 QSS-8-F 153151 NPQP-T-Q8-E-FD-P10 NPQP-Y-R12-Q12-FD QSF-1/4-8-B QSY-6H-4 VABM-B10-25S-G38-6-P3 153367 NPQP-LQ-R18-Q8-FD-P10 QS-1/8-8-I QSLL-G1/2-12 SASC-P4-A-M8-A VABM-B10-25S-G38-10 153031 NPQP-D-Q4-S8-FD-P10 QS-1/2-16 NPQP-L-Q10-E-FD-P10 NPQP-Y-Q6-E-FD-P10 153269 153307 NPQP-LQ-R18-Q4-FD-P10 QS-10H-6 VBQF-U-G14-E SGS-M10X1,25 DSBC-80-20-D3-PPSA-N3 NPQH-T-Q14-E-P10 QSF-3/8-8-B