

SESUC5VD2510-10U

Features

- DFN2510 package
- Protects up to 4-Lines operating at 5V
- R2R + Zener technology
- Low clamping voltage
- Low leakage current
- Ultra low capacitance (0.15pF typical I/O to I/O)
- ESD Protection for high-speed data lines to:
  IEC 61000-4-2 ±8KV contact ±15KV air
- RoHS compliant



DFN2510



Schematic Diagram

Applications

- USB 3.0/3.1
- HDMI 1.4/2.0, Display Port 1.3, eSATA
- Unified Display Interface (UDI)
- Digital Visual Interface (DVI)
- High speed serial interfaces

Absolute Maximum Ratings

(T_A=25℃, Unless otherwise specified.)

Parameter	Symbol	Value	Unit
Junction Temperature	T_J	-55 to +125	℃
Storage Temperature	T_{STG}	-55 to +150	℃
Lead Soldering Temperature	T_L	260 (10sec.)	℃
Peak Pulse Current (t_P = 8/20μS)	I_{PP}	3	A
IEC 61000-4-2 Contact (ESD)	VESD	±8	kV
IEC 61000-4-2 Air (ESD)	VESD	±15	kV

Electrical Characteristics

(T_A=25℃, Unless otherwise specified.)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Reverse stand-off Voltage	V_{RWM}				5	V
Reverse Breakdown Voltage	V_{BR}	I_T=1mA	6	7.2	9.5	V
Reverse Leakage Current	I_R	V_R=5V		0.01	1	μA
Clamping Voltage (IEC 61000-4-5)	V_C	I_{PP}=3A，T_P=8/20μS		10		V
Trigger Voltage (IEC 61000-4-2)	V_T	V_{ESD} =8kV		135		V
Clamping Voltage (IEC 61000-4-2)	V_C	V_{ESD} =8kV		20		V
Junction Capacitance	C_J	V_R=0V,f=1MHz, I/O to I/O		0.15		pF
	C_J	V_R=0V,f=1MHz, I/O to GND		0.35		pF

@copyright Semitel 2016

Typical Characteristic Curves

Fig.1 Pulse Waveform-ESD(IEC61000-4-2)




Fig.3 IEC61000-4-2 +8kV Contact ESD Clamping Waveform




Fig.5 Eye Diagram - USB3.1 at 10Gbps per channel (with SESUC5VD2510-10U)






Fig.6 Insertion Loss S21 - I/O to I/O




@copyright Semitel 2016

Product Dimensions




Symbol	Dimensions in millimeters		
	Min	Nom	Max
A	0.45	0.50	0.55
A1	-	0.02	0.05
A3	0.10	0.15	0.20
D	2.45	2.50	2.55
E	0.95	1.00	1.05
D1	0.35	0.40	0.45
b	0.15	0.20	0.25
e	0.50BSC		
L	0.35	0.40	0.45

Part Number System



Marking



@copyright Semitel 2016

Order Information

Device	Package	Carrier	Quantity	HSF Status
SESUC5VD2510-10U	DFN2510	Tape & Reel (7")	3000pcs / Reel	RoHS Compliant

Revision history

Date	Revision	Description of changes
26-January-2016	**A0**	**First issue**

@copyright Semitel 2016

CAUTION / WARNING

• Information in this document is believed to be accurate and reliable. However, SEMITEL does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

• Users should independently evaluate the suitability of and test each product selected for their own applications, and SEMITEL assumes no liability whatsoever relating to the choice, selection or use of the SEMITEL products and services described herein.

• SEMITEL reserves the right to change or update, without notice, any information contained in this publication; to change, without notice, the design, construction, processing, or specification of any product; and to discontinue or limit production or distribution of any product.

• Information in this document supersedes and replaces all information previously supplied.

• Products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an SEMITEL product can reasonably be expected to result in personal injury, death or severe property or environmental damage. SEMITEL accepts no liability for inclusion and/or use of SEMITEL products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

• This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

• Resale of SEMITEL products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by SEMITEL for the SEMITEL product or service described herein and shall not create or extend in any manner whatsoever, any liability of SEMITEL.

• SEMITEL expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. SEMITEL only obligations are those in the SEMITEL Standard Terms and Conditions of Sale and in no case will SEMITEL be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.

Specifications are subject to change without notice

© Copyright 2005, Semitel Electronics
Semitel . ® is a registered trademark of Semitel Electronics
All rights reserved

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Semitel:

ESDPSD2510V12 ESDPSD2510V15 SESUC5VD0603PSN-2B SES3V3D1006-2B SES8VD1006-2B SESUC5VD882SY-2B ESDPSA0402V12 SESUC3V3D2510-10U ESDPSA0402V15 SESUC3V3D882-2B SESUC3V3E0201SN-2B SESUC5VD1006SN-2B SESUC5VD2510-10U ESDPSA0402V30 ESDPSD2510V24 MLSEP15B-0603 SES5VD923-2U SES6V3D1006-2U SESLC5VD882S-2B ESDPSA0201V24 ESDPSA0603V09 SES12VD523-2B SES5VD323-2B SES5VD882-2B SESLC3V3D323S-2B SESUC5VD2510SN-10U ESDPSA0603V15 ESDPSD2510V30 MLSEP30B-0603 SESUC3V3D0603-2B