Heatsinks f.cool

- Profile heatsinks and fluid coolers
  - Standard extruded heatsinks
  - Extruded heatsinks for lock-in retaining spring
  - Extruded heatsinks for PCB mounting
  - Extruded heatsinks for DC/DC converter
  - Retaining springs for transistors
  - U-Extruded heatsinks
  - Die-cast heatsinks
  - Fin coolers
  - Fluid coolers
  - Aluminium flat-, quadrangular-, angled-, U- & T-profiles
- Heatsinks and active heatsinks for processors
- Finger-shaped heatsinks
- Cooling aggregates
- Accessories components

Cooling aggregates

Cases f.case


Connectors f.con

Standard extruded heatsinks

SK 100 75 SA

66 x 40 mm

add to request



Features | Technical Drawing | Service

width	66 mm
heigth	40 mm
plate thickness	10 mm
lengths	100 mm
R_{th}	1 - 2.9 K/W
surface	black anodised

Fischer Elektronik GmbH & Co. KG
Nottebohmstraße 28, D - 58511 Lüdenscheid
Ph: +49 (0) 23 51 / 4 35 - 0, info@fischerelektronik.de

http://www.fischerelektronik.de/web_fischer/en_GB/heatsinks/D/Cooling%20aggregates/index.xhtml#clsFischer@D

Internet | 110%

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Fischer Elektronik:

SK 85 50 SA SK 88 50 SA SK68-37,5-SA MS 53 3 SK0937,5TO220 SL 22 112 72 G THFK247
CC 35 67 100 ME FK 245 MI 247 H LA 7/150 24V SK 58 50 SA SK 104 38,1 STS SK68-50SA
TUF 80 42 100 SA BLY 1 50 Z FK 244 13 D2 PAK TO-263 (D2PAK) WLK 5 FK 247 220 MI TO 220 KL35050
LA 17/200 24V FK 224 SA P SIP P SIP FK 240 SA 220 V SK 04 100 SA SL 11 190 36 G SL22 124-16G
WKT 300 FK 232 220 SA LA ICK 17 X17 W 12V SK 198 1000 AL SK 85 100 SA