

Standard cylinder
DSNU-16-15-P-A

Part number: 1908259
★ Core product range

FESTO





Data sheet

Feature	Value
Stroke	15 mm
Piston diameter	16 mm
Piston rod thread	M6
Cushioning	P: Flexible cushioning rings/plates at both ends
Assembly position	Any
Conforms to standard	CETOP RP 52 P ISO 6432
Piston-rod end	Male thread
Design structure	Piston Piston rod Cylinder barrel
Position detection	For proximity sensor
Variants	Single-ended piston rod
Working pressure	1 ... 10 bar
Mode of operation	double-acting
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Ambient temperature	-20 ... 80 °C
Maritime classification	see certificate
Impact energy in end positions	0.15 J

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

QSML-6 153031 QS-1/8-8-I QSY-6H-4 SASC-P4-A-M8-A HGL-1/8-QS-6 NPQP-LQ-R18-Q4-FD-P10 NPQP-Y-R12-Q12-FD QSF-1/4-8-B VABM-B10-25S-G38-6-P3 153269 NPQH-T-Q14-E-P10 QS-10H-6 QSS-8-F SGS-M10X1,25 VABM-B10-25S-G38-10 VBQF-U-G14-E 153307 QS-1/2-16 QSF-3/8-8-B 153151 CRVZS-0.4 DSBC-80-20-D3-PPSA-N3 NPQP-LQ-R18-Q8-FD-P10 NPQP-D-Q4-S8-FD-P10 NPQP-T-Q8-E-FD-P10 NPQP-Y-Q6-E-FD-P10 QSLL-G1/2-12 153367 NPQP-L-Q10-E-FD-P10