Description

The IRLR8113PBF uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 4.5V. This device is suitable for use as a Battery protection or in other Switching application.



TO-252-2L
(TO-252(DPAK))

General Features

V_{DS} = 30V I_D = 80A

$R_{DS(ON)}$ < 6.8mΩ @ V_{GS}=10V

Application

Battery protection

Load switch

Uninterruptible power supply



N-Channel MOSFET

Package Marking and Ordering Information

Product ID	Pack	Brand	Qty(PCS)
IRLR8113PBF	TO-252-2L(TO-252(DPAK))	HXY MOSFET	2500

Absolute Maximum Ratings (T_C=25°C unless otherwise noted)

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	±20	V
I_D	Drain Current – Continuous (T_C=25°C)	80	A
	Drain Current – Continuous (T_C=100°C)	51	A
I_{DM}	Drain Current – Pulsed[1]	320	A
EAS	Single Pulse Avalanche Energy[2]	88	mJ
IAS	Single Pulse Avalanche Current[2]	42	A
P_D	Power Dissipation (T_C=25°C)	54	W
	Power Dissipation – Derate above 25°C	0.43	W/°C
T_{STG}	Storage Temperature Range	-55 to 150	°C
T_J	Operating Junction Temperature Range	-55 to 150	°C
$R_{\theta JA}$	Thermal Resistance Junction to ambient	62	°C/W
$R_{\theta JC}$	Thermal Resistance Junction to Case	2.3	°C/W

Electrical Characteristics (T_J=25 °C, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BVDSS	Drain-Source Breakdown Voltage	V_{GS}=0V , I_D=250uA	30	---	---	V
△BVDSS/△TJ	BV_{DSS} Temperature Coefficient	Reference to 25℃ , I_D=1mA	---	0.04	---	V/℃
IDSS	Drain-Source Leakage Current	V_{DS}=30V , V_{GS}=0V , T_J=25℃	---	---	1	uA
		V_{DS}=24V , V_{GS}=0V , T_J=125℃	---	---	10	uA
IGSS	Gate-Source Leakage Current	V_{GS}=±20V , V_{DS}=0V	---	---	±100	nA
RDS(ON)	Static Drain-Source On-Resistance[3]	V_{GS}=10V , I_D=20A	---	5	6.8	mΩ
		V_{GS}=4.5V , I_D=10A	---	6.5	9	mΩ
VGS(th)	Gate Threshold Voltage	V_{GS}=V_{DS} , I_D =250uA	1	1.6	2.5	V
△$V_{GS(th)}$	$V_{GS(th)}$ Temperature Coefficient		---	-4	---	mV/℃
gfs	Forward Transconductance	V_{DS}=10V , I_D=10A	---	18	---	S
Q_g	Total Gate Charge[3,4]	V_{DS}=15V , V_{GS}=4.5V , I_D=20A	---	11.1	---	nC
Qgs	Gate-Source Charge[3,4]		---	1.85	---	
Qgd	Gate-Drain Charge[3,4]		---	6.8	---	
Td(on)	Turn-On Delay Time[3,4]	V_{DD}=15V , V_{GS}=10V , R_G=3.3Ω I_D=15A	---	7.5	---	ns
T_r	Rise Time[3,4]		---	14.5	---	
Td(off)	Turn-Off Delay Time[3,4]		---	35.2	---	
T_f	Fall Time[3,4]		---	9.6	---	
Ciss	Input Capacitance	V_{DS}=25V , V_{GS}=0V , F=1MHz	---	1160	---	pF
Coss	Output Capacitance	V_{GS}=0V, V_{DS}=0V, F=1MHz	---	200	---	Ω
Crss	Reverse Transfer Capacitance		---	180	---	
R_g	Gate resistance		---	2.5	---	
EAS	Single Pulse Avalanche Energy	V_{DD}=25V, L=0.1mH, IAS=20A	20	---	---	mJ
IS	Continuous Source Current	V_G=V_D=0V , Force Current	---	---	80	A
ISM	Pulsed Source Current[3]		---	---	320	A
VSD	Diode Forward Voltage[3]	V_{GS}=0V , I_S=1A , T_J=25℃	---	---	1	V
trr	Reverse Recovery Time	VGS=0V,IS=1A , di/dt=100A/μs T_J=25℃	---	---	---	ns
Q_{rr}	Reverse Recovery Charge		---	---	---	nC

Typical Characteristics



Fig.1 Continuous Drain Current vs. Tc



Fig.2 Normalized RDSON vs. Tj



Fig. 3 Normalized Vth vs. Tj



Fig. 4 Gate Charge Waveform



Fig.5 Normalized Transient Impedance



Fig.6 Maximum Safe Operation Area



Fig. 7 Switching Time Waveform



Fig. 8 EAS Waveform

TO252-2L(TO-252(DPAK)) Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.660	0.860	0.026	0.034
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	0.483 TYP.		0.190 TYP.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.800	10.400	0.386	0.409
L1	2.900 TYP.		0.114 TYP.	
L2	1.400	1.700	0.055	0.067
L3	1.600 TYP.		0.063 TYP.	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.350 TYP.		0.211 TYP.	

Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HXY MOSFET:

MMBT3904T TPSMB28A-VR IRLML6246PBF P6SMB36CA HOPA2340UA HT7540-1 HXY2101EI HXY2300MI HESDNC5VB1AF-B HMCP602-I/SN SS510C US2M BZT52C13 MAX487ESA PESD5V0S1BB SD15C HT7150 HXY8205ES P6SMB200A TPSMB100CA-VR SS1045 SS5150B DTC143ZE HAD8542ARZ SS10100 BZT52C3V3S HC3D10170A HC4D20120A P6SMB33CA SQJA04EP-T1_BE3