Description


This single buffer/driver is designed for 1.65-V to 5.5-V VCC operation.



The output of the 74LVC1G07Gx,125 device is open drain and can be connected to other open-drain outputs to implement active-low wired-OR or active high wired-AND functions. The maximum sink current is 32 mA.

Features

- Supports 5-V VCC Operation
- Input and Open-Drain Output Accept Voltages up to 5.5 V
- Can Translate Up or Down
- Low Power Consumption, 10-μA Max ICC
- ±24-mA Output Drive at 3.3 V
- Ioff Supports Live Insertion, Partial-Power Down Mode, and Back-Drive Protection

Connection Diagrams and Pin Description

PIN DESCRIPTION	MARKING
 SOT23-5	

PIN DESCRIPTION	MARKING
 SC70-5	

PIN No. DBV/DCK	NAME	I/O	FUNCTION
1	NC		No Connected
2	A	I	Input
3	GND		Ground
4	Y	O	Output
5	VCC		Supply Voltage

ORDER INFORMATION

ORDERING NUMBER	PACKAGE	PACKING OPTION
74LVC1G07GV,125	SOT23-5	3000PCS
74LVC1G07GW,125	SC70-5	3000PCS

Logic Diagram




Figure 3.1：74LVC1G07Gx,125 Logic Diagram

Function Table

Input	Output
A	Y
1	Z
0	0

X = don’t care, 1≡High State, 0≡Low State,Z=High Impedance

Absolute Maximum Ratings

Symbol	Parameter	MIN	MAX	Unit
V_{CC}	Supply Voltage	-0.5	6.5	V
V_I	Input Voltage Range	-0.5	6.5	V
V_O	Voltage Range(applied to any output in the high-impedance or power-off state)(1)	-0.5	6.5	V
	Voltage Range(applied to any output in the high or low state)	-0.5	VCC + 0.5	V
I_O	Continuous Output Current		±50	mA
T_J	Junction Temperature		125	℃
T_{OP}	Operating Temperature	0	70	℃

Absolute maximum ratings are those values beyond which the device could be permanently damaged,These are stress ratings only,which do not imply functional operation of the device at these or any other conditions beyond those indicated under normal operating conditions.

(1) The input and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.

Electrical Characteristics

DC Specifications

(T_a=25℃ , voltages are referenced to GND (ground=0V), unless otherwise specified)

Symbol	Parameter	Test Condition	MIN	TYP	MAX	Unit
V_{IH}	High Level Input Voltage	V_{CC}=1.65V to 1.95V	0.65V_{CC}	--	--	V
		V_{CC}=2.3V to 2.7V	1.7	--	--	V
		V_{CC}=3V to 5.5V	0.7V_{CC}	--	--	V
V_{IL}	Low Level Input Voltage	V_{CC}=1.65V to 1.95V	--	--	0.35V_{CC}	V
		V_{CC}=2.3V to 2.7V	--	--	0.7	V
		V_{CC}=3V to 3.6V	--	--	0.8	V
		V_{CC}=4.5V to 5.5V	--	--	0.3V_{CC}	V
I_{OL}	Low Level Output Current	V_{CC}=1.65V	--	--	4	mA
		V_{CC}=2.3V	--	--	8	mA
		V_{CC}=3V	--	--	16	mA
			--	--	24	mA
		V_{CC}=4.5V	--	--	32	mA

Symbol	Parameter	Test Condition	MIN	TYP	MAX	Unit
V_{OL}	Low Level Output Voltage	V_{CC}=1.65V to 5.5V,I_{OH}=100uA	--	--	0.1	V
		V_{CC}=1.65V,I_O=4mA	--	0.09	--	V
		V_{CC}=2.3V,I_O=8mA	--	0.1	--	V
		V_{CC}=3V,I_O=16mA	--	0.15	--	V
		V_{CC}=3V,I_O=24mA	--	0.25	--	V
		V_{CC}=4.5V,I_O=32mA	--	0.25	--	V
I_I	A Inputs Leakage Current	V_{CC}=0 to 5.5V,V_I=V_{CC} or GND	--	0	±1	uA
I_{off}	Power Off Leakage Current	V_{CC}=0V,V_I or V_O=5.5V	--	0	±10	uA
I_{OZ}	3-State Output OFF-State Current	V_{CC}=3.6V, V_O = 0 to 5.5V	--	0	10	uA
I_{CC}	Quiescent Supply Current	V_{CC}=1.65V to 5.5V,V_I=V_{CC} or GND,I_O=0	--	0	10	uA
ΔI_{CC}	Additional Quiescent Supply Current Per Input Pin	V_{CC}=3V to 5.5V,one input at V_{CC} -0.6V,Other inputs at V_{CC} or GND	--	--	500	uA

Application Information





Figure 5.1：Application Schematic

PACKAGE DESCRIPTION


SOT-23-5




TOP VIEW

5LD SOT-23 PACKAGE OUTLINE DIMENSIONS

Dimension	Min.	Max.
A	1.05	1.35
A1	0.04	.15
B	0.3	0.5
C	0.09	0.2
D	2.8	3.0
H	2.5	3.1
E	1.5	1.7
e	0.95 REF.	
e1	1.90 REF.	
L1	0.2	0.55
L	0.35	0.8
Q	0°	10°



FRONT VIEW




SIDE VIEW

NOTE:

1.DIMENSIONS ARE IN MLLIMETERS
2.DRAWING NOT TO SCALE
3.DIMENSIONS ARE INCLUSIVE OF PLATING
4.DIMENSIONS ARE EXCLUSVE OF MOLD FLASH AND METAL BURR

SC70-5



Symbol	Dim in mm		
	MIN	TYP	MAX
A	0.90	1.00	1.10
A1	0.00	0.05	0.10
A2	0.90	0.95	1.00
b	0.15	0.25	0.35
C	0.10	0.12	0.15
D	1.80	2.00	2.20
E	2.15	2.25	2.35
E1	1.15	1.25	1.35
e	0.650TYP.		
el	1.20	1.30	1.40
L	0.25	0.30	0.40
L2	0.15TYP.		
Y	0.00	0.05	0.10
θ	4°	8°	12°