Data Sheet

HUBER+SUHNER

Coaxial Cable Connector
11_BNC-50-3-4/133_N

Description

Straight cable plug



Interface standards
IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0103 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00006208
Catalogue drawing	DCA-00006196
Assembly instruction	DOC-0000179061

Ordering Information

Bulk 100 pcs package	11_BNC-50-3-4/133_NH
Single package	11_BNC-50-3-4/133_NE

Additional Information

Suitable cables	RG_58_C/U, GX_03272

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Huber+Suhner:

PCRS_LCMX_LCMX_O421T_30.0_LL 11_TNC-50-3-116/133_NE 23000457 23002145
6601_PC185-50-1/199_NE 11MMBXEF31616MMBX/300 11_SMC-50-2-10/111_NE 1399.17.0231 84093961
84118385 MINIBEND R-12 RADOX 125 0.75 MMÂ² RED 12012090 33_PC24-SK-50-2/199_NE
G032D/BNCm/BNCm/1000 MINIBEND R-8 12535682 1399.31.0020 6806.19.A Minibend L-10
16_MMCX-50-2-4/111_OH 6620_SMA-50-2/199_NE 1399.17.0210 24_SMA-50-2-15/111_NH 85201112
G032D/Nm/SMAm/1000 RG_196_A/U 22511964 G_03130_HT-01 MINIBEND R-10