TOSHIBA CMOS Digital Integrated Circuit Silicon Monolithic

TC74LCX273F, TC74LCX273FK

Low-Voltage Octal D-Type Flip-Flop with Clear with 5-V Tolerant Inputs and Outputs


The TC74LCX273 is a high-performance CMOS octal D-type flip-flop. Designed for use in 3.3-V systems, it achieves high-speed operation while maintaining the CMOS low-power dissipation.

The device is designed for low-voltage (3.3 V) V_{CC} applications, but it could be used to interface to 5-V supply environment for both inputs and outputs.

This 8 bit D-type flip-flop is controlled by a clock input (CK) and a clear input ($\overline{CLR}$). When the $\overline{CLR}$ input is low, the eight outputs are at a low logic level.


All inputs are equipped with protection circuits against static discharge.

TC74LCX273F



SOP20-P-300-1.27A

TC74LCX273FK



VSSOP20-P-0030-0.50

Weight

SOP20-P-300-1.27A : 0.22 g (typ.)

VSSOP20-P-0030-0.50 : 0.03 g (typ.)

Features


- Low-voltage operation: V_{CC} = 1.65 to 3.6 V
- High-speed operation: t_{pd} = 8.5 ns (max) (V_{CC} = 3.0 to 3.6 V)
- Output current: $|I_{OH}|/I_{OL}$ = 24 mA (min) (V_{CC} = 3.0 V)
- Available in JEITA SOP, VSSOP (US)
- Power-down protection is provided on all inputs and outputs
- Pin and function compatible with the 74 series (74AC/VHC/HC/F/ALS/LS etc.) 273 type

Note: The Electrical Characteristics of V_{CC} = 1.8 ± 0.15 V is only applicable for products which manufactured from January 2009 onward.


Start of commercial production
2000-02

© 2018-2021
Toshiba Electronic Devices & Storage Corporation

Pin Assignment (top view)



IEC Logic Symbol




Truth Table

Inputs			Outputs	Function
$\overline{CLR}$	D	CK	Q	
L	X	X	L	Clear
H	L	↑	L	—
H	H	↑	H	—
H	X	↓	Qn	No change

X: Don't care

System Diagram



© 2018-2021
Toshiba Electronic Devices & Storage Corporation

Absolute Maximum Ratings (Note 1)

Characteristics	Symbol	Rating	Unit
Power supply voltage	V_{CC}	−0.5 to 7.0	V
DC input voltage	V_{IN}	−0.5 to 7.0	V
DC output voltage	V_{OUT}	−0.5 to 7.0 (Note 2)	V
		−0.5 to V_{CC} + 0.5 (Note 3)	
Input diode current	I_{IK}	−50	mA
Output diode current	I_{OK}	±50 (Note 4)	mA
DC output current	I_{OUT}	±50	mA
Power dissipation	P_D	180	mW
DC V_{CC}/ground current	I_{CC}/I_{GND}	±100	mA
Storage temperature	T_{stg}	−65 to 150	°C

Note 1: Exceeding any of the absolute maximum ratings, even briefly, lead to deterioration in IC performance or even destruction.
Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings and the operating ranges.
Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook (“Handling Precautions”/“Derating Concept and Methods”) and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Note 2: V_{CC} = 0 V

Note 3: High or low state. I_{OUT} absolute maximum rating must be observed.

Note 4: $V_{OUT} < GND$, $V_{OUT} > V_{CC}$

Operating Ranges (Note 1)

Characteristics	Symbol	Rating	Unit
Power supply voltage	V_{CC}	1.65 to 3.6	V
		1.5 to 3.6 (Note 2)	
Input voltage	V_{IN}	0 to 5.5	V
Output voltage	V_{OUT}	0 to 5.5 (Note 3)	V
		0 to V_{CC} (Note 4)	
Output current	I_{OH}/I_{OL}	±24 (Note 5)	mA
		±12 (Note 6)	
Operating temperature	T_{opr}	−40 to 85	°C
Input rise and fall time	dt/dv	0 to 10 (Note 7)	ns/V

Note 1: The operating ranges must be maintained to ensure the normal operation of the device.
Unused inputs must be tied to either V_{CC} or GND.

Note 2: Data retention only

Note 3: V_{CC} = 0 V

Note 4: High or low state

Note 5: V_{CC} = 3.0 to 3.6 V

Note 6: V_{CC} = 2.7 to 3.0 V

Note 7: V_{IN} = 0.8 to 2.0 V, V_{CC} = 3.0 V

© 2018-2021
Toshiba Electronic Devices & Storage Corporation

Electrical Characteristics

DC Characteristics (Ta = –40 to 85°C)

Characteristics		Symbol	Test Condition		V_{CC} (V)	Min	Max	Unit
Input voltage	H-level	V_{IH}			1.65 to 2.3	V_{CC} × 0.9	—	V
					2.3 to 2.7	1.7	—	
					2.7 to 3.6	2.0	—	
	L-level	V_{IL}			1.65 to 2.3	—	V_{CC} × 0.1	
					2.3 to 2.7	—	0.7	
					2.7 to 3.6	—	0.8	
Output voltage	H-level	V_{OH}	V_{IN} = V_{IH} or V_{IL}	I_{OH} = –100 μA	1.65 to 3.6	V_{CC} – 0.2	—	V
				I_{OH} = –4 mA	1.65	1.05	—	
				I_{OH} = –8 mA	2.3	1.7	—	
				I_{OH} = –12 mA	2.7	2.2	—	
				I_{OH} = –18 mA	3.0	2.4	—	
				I_{OH} = –24 mA	3.0	2.2	—	
	L-level	V_{OL}	V_{IN} = V_{IH} or V_{IL}	I_{OL} = 100 μA	1.65 to 3.6	—	0.2	
				I_{OL} = 4 mA	1.65	—	0.45	
				I_{OL} = 8 mA	2.3	—	0.7	
				I_{OL} = 12 mA	2.7	—	0.4	
				I_{OL} = 16 mA	3.0	—	0.4	
				I_{OL} = 24 mA	3.0	—	0.55	
Input leakage current		I_{IN}	V_{IN} = 0 to 5.5 V		1.65 to 3.6	—	±5.0	μA
Power-off leakage current		I_{OFF}	V_{IN}/V_{OUT} = 5.5 V		0	—	10.0	μA
Quiescent supply current		I_{CC}	V_{IN} = V_{CC} or GND		1.65 to 3.6	—	10.0	μA
			V_{IN} = 3.6 to 5.5 V		1.65 to 3.6	—	±10.0	
Increase in I_{CC} per input		ΔI_{CC}	V_{IN} = V_{CC} – 0.6 V (per 1 input)		2.7 to 3.6	—	500	

© 2018-2021
Toshiba Electronic Devices & Storage Corporation

AC Characteristics (Ta = –40 to 85°C)

Characteristics	Symbol	Test Condition	V_{CC} (V)	Min	Max	Unit
Maximum clock frequency	f_{MAX}	(Figure 1, Figure 2)	1.8 ± 0.15	50	—	MHz
			2.5 ± 0.2	100	—	
			2.7	150	—	
			3.3 ± 0.3	150	—	
Propagation delay time (CK-Q)	t_{PLH} t_{PHL}	(Figure 1, Figure 2)	1.8 ± 0.15	—	30.0	ns
			2.5 ± 0.2	—	10.5	
			2.7	—	9.5	
			3.3 ± 0.3	1.5	8.5	
Propagation delay time ($\overline{CLR}$ -Q)	t_{PHL}	(Figure 1, Figure 3)	1.8 ± 0.15	—	30.0	ns
			2.5 ± 0.2	—	10.5	
			2.7	—	9.5	
			3.3 ± 0.3	1.5	8.5	
Minimum pulse width (CK)	$t_{w\ (H)}$ $t_{w\ (L)}$	(Figure 1, Figure 2)	1.8 ± 0.15	10.0	—	ns
			2.5 ± 0.2	5.0	—	
			2.7	3.3	—	
			3.3 ± 0.3	3.3	—	
Minimum pulse width ($\overline{CLR}$)	$t_{w\ (L)}$	(Figure 3)	1.8 ± 0.15	10.0	—	ns
			2.5 ± 0.2	5.0	—	
			2.7	3.3	—	
			3.3 ± 0.3	3.3	—	
Minimum setup time	t_s	(Figure 1, Figure 2)	1.8 ± 0.15	10.0	—	ns
			2.5 ± 0.2	5.0	—	
			2.7	2.5	—	
			3.3 ± 0.3	2.5	—	
Minimum hold time	t_h	(Figure 1, Figure 2)	1.8 ± 0.15	1.5	—	ns
			2.5 ± 0.2	1.5	—	
			2.7	1.5	—	
			3.3 ± 0.3	1.5	—	
Minimum removal time	t_{rem}	(Figure 4)	1.8 ± 0.15	8.0	—	ns
			2.5 ± 0.2	4.0	—	
			2.7	2.5	—	
			3.3 ± 0.3	2.0	—	
Output to output skew	t_{osLH} t_{osHL}	(Note)	2.7	—	—	ns
			3.3 ± 0.3	—	1.0	

Note: Parameter guaranteed by design.
($t_{osLH} = |t_{pLHm} - t_{pLHn}|$, $t_{osHL} = |t_{pHLm} - t_{pHLn}|$)

© 2018-2021
Toshiba Electronic Devices & Storage Corporation

Dynamic Switching Characteristics

(Ta = 25°C, input: $t_r = t_f$ = 2.5 ns, C_L = 50 pF, R_L = 500 Ω)

Characteristics	Symbol	Test Condition	V_{CC} (V)	Typ.	Unit
Quiet output maximum dynamic V_{OL}	V_{OLP}	V_{IH} = 3.3 V, V_{IL} = 0 V	3.3	0.8	V
Quiet output minimum dynamic V_{OL}	$\lvert V_{OLV} \rvert$	V_{IH} = 3.3 V, V_{IL} = 0 V	3.3	0.8	V

Capacitive Characteristics (Ta = 25°C)

Characteristics	Symbol	Test Condition	V_{CC} (V)	Typ.	Unit
Input capacitance	C_{IN}	—	3.3	7	pF
Output capacitance	C_{OUT}	—	0	8	pF
Power dissipation capacitance	C_{PD}	f_{IN} = 10 MHz (Note)	3.3	25	pF

Note: C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption.
Average operating current can be obtained by the equation:
$I_{CC\ (opr)} = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}/8$ (per bit)

AC Test Circuit




Figure 1

AC Waveform




Figure 2 t_{pLH}, t_{pHL}, t_w, t_s, t_h

© 2018-2021
Toshiba Electronic Devices & Storage Corporation




Figure 3 t_{pHL}





Figure 4 t_{rem}

	Symbol	V_{CC}		
		3.3 ± 0.3 V 2.7 V	2.5 ± 0.2 V	1.8 ± 0.15 V
Input	V_{IH}	2.7 V	V_{CC}	V_{CC}
	V_{IM}	1.5 V	$V_{CC}/2$	$V_{CC}/2$
	t_r, t_f	2.5 ns	2.0 ns	2.0 ns
Output	V_{OM}	1.5 V	$V_{OH}/2$	$V_{OH}/2$
Load	C_L	50 pF	30 pF	30 pF
	R_L	500 Ω	500 Ω	1 kΩ

© 2018-2021
Toshiba Electronic Devices & Storage Corporation

Package Dimensions

SOP20-P-300-1.27A Unit: mm




Weight: 0.22 g (typ.)

© 2018-2021
Toshiba Electronic Devices & Storage Corporation

Package Dimensions

VSSOP20-P-0030-0.50 Unit: mm



Weight: 0.03 g (typ.)

© 2018-2021
Toshiba Electronic Devices & Storage Corporation

RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as “TOSHIBA”.
Hardware, software and systems described in this document are collectively referred to as “Product”.

- TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, lifesaving and/or life supporting medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, and devices related to power plant. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative or contact us via our website.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**

© 2018-2021
Toshiba Electronic Devices & Storage Corporation

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TOSHIBA:

1SS361FV,L3F(T CEZ6V8,L3F SSM6L36FE,LM(T TC7SZU04F,LJ(CT TK7R7P10PL,RQ(S2 TK100E10N1,S1X(S TK7P60W,RVQ(S TLP4176G(TP,M,F) TPW3R70APL,L1Q(M DF2S6.8MFS,L3M(T DF3A5.6FU(TE85L,F) TB6588FG,8,EL,JU TC78H651FNG,EL TLP2704(TP,E(T TC75S63TU,LF(T TC7W08FU,LF(T 2SC2712-Y,LF(T TBC847B,LM(T TC7SH04FU,LJ(CT TCKE805NA,RF(S TDS4B212MX,ELF(S TC7WZ08FK,LJ(CT TLP3412SRLA(TP,E(O TLP385(GB-TPL,E(T CES520,L3F(T RN4985,LF(CT TCR2LE36,LM(CT SSM3J358R,LF(T TC7S32F,LF(T TLP2710(TP,E(T