★ Green Device Available
★ Super Low Gate Charge
★ Excellent Cdv/dt effect decline
★ Advanced high cell density Trench technology

Product Summary

BVDSS	RDSON	ID
30V	24mΩ	5.8A

Description

The DMN3042L-7 is the high cell density trenched N-ch MOSFETs, which provides excellent RDSON and efficiency for most of the small power switching and load switch applications.

The DMN3042L-7 meet the RoHS and Green Product requirement with full function reliability approved.

SOT23-3L Pin Configuration





Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction-ambient [1]	---	96	˚C/W
$R_{\theta JC}$	Thermal Resistance Junction-Case[1]	---	---	˚C/W

Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	±12	V
I_D@T_A=25˚C	Continuous Drain Current, V_{GS} @ 10V[1]	5.8	A
I_D@T_A=70˚C	Continuous Drain Current, V_{GS} @ 10V[1]	4.1	A
I_{DM}	Pulsed Drain Current[2]	20.4	A
P_D@T_A=25˚C	Total Power Dissipation[3]	1.4	W
T_{STG}	Storage Temperature Range	-55 to 150	˚C
T_J	Operating Junction Temperature Range	-55 to 150	˚C

Electrical Characteristics (T_J=25℃ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D=250μA	30	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=30V, V_{GS}=0V,	-	-	1.0	μA
I_{GSS}	Gate to Body Leakage Current	V_{DS}=0V, V_{GS}= ±12V	-	-	±100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=250μA	0.5	-	1.3	V
$R_{DS(on)}$	Static Drain-Source on-Resistance note2	V_{GS}=10V, I_D=4A	-	24	31	mΩ
		V_{GS}=4.5V, I_D=3A	-	27	38	
		V_{GS}=2.5V, I_D=3A	-	36	54	
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS}=15V, V_{GS}=0V, f=1.0MHz	-	507	-	pF
C_{oss}	Output Capacitance		-	52	-	pF
C_{rss}	Reverse Transfer Capacitance		-	43	-	pF
Q_g	Total Gate Charge	V_{DS}=15V, I_D=5A, V_{GS}=4.5V	-	9.1	-	nC
Q_{gs}	Gate-Source Charge		-	2.1	-	nC
Q_{gd}	Gate-Drain(“Miller”) Charge		-	2.8	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	V_{DS}=15V,R_{GEN}=3Ω, R_L=2.8Ω, V_{GS}=10V	-	3	-	ns
t_r	Turn-on Rise Time		-	2.8	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	25	-	ns
t_f	Turn-off Fall Time		-	4	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current		-	-	5	A
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	20	A
V_{SD}	Drain to Source Diode Forward Voltage	V_{GS}=0V, I_S=5A	-	-	1.2	V

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. Pulse Test: Pulse Width≤300μs, Duty Cycle≤0.5%

Typical Performance Characteristics

Figure1: Output Characteristics



Figure 2: Typical Transfer Characteristics



Figure 3: On-resistance vs. Drain Current



Figure 4: Body Diode Characteristics



Figure 5: Gate Charge Characteristics



Figure 6: Capacitance Characteristics



Figure 7: Normalized Breakdown Voltage vs. Junction Temperature



Figure 8: Normalized on Resistance vs. Junction Temperature



Figure 9: Maximum Safe Operating Area



Figure 10: Maximum Continuous Drain Current vs. Ambient Temperature



Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



SOT-23-3L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°