TECH PUBLIC
台舟电子

AZ5123-01H-P

1-Line Bi-directional TVS Diode

www.sot23.com.tw

Features

- Low operating voltage: ±3.3V
- Ultra low capacitance: 13pF typical
- Ultra low leakage: nA level
- Low clamping voltage
- 2-pin leadless package
- Complies with following standards:
- - IEC 61000-4-2 (ESD) immunity test
  Air discharge: ±30kV
  Contact discharge: ±30kV
  – IEC61000-4-5 (Lightning) 8A (8/20μs)
- These are Pb–Free Devices
- Response Time is Typically < 1 ns


Mechanical Characteristics

- Package: SOD523 (0603)
- Lead Finish: Matte Tin
- Case Material: “Green” Molding Compound.
- Moisture Sensitivity: Level 3 per J-STD-020
- Terminal Connections: See Diagram Below
- Shipping Qty :3000pcs/7Inch Tape & Reel

Applications

- Cellular Handsets and Accessories
- Personal Digital Assistants
- Notebooks and Handhelds
- Portable Instrumentation
- Digital Cameras
- Peripherals

Dimensions and Pin Configuration



Marking: eB

SOD523

Absolute Maximum Ratings (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μs)	Ppk	90	W
Peak Pulse Current (8/20μs)	Ipp	8	A
ESD per IEC 61000−4−2 (Air) ESD per IEC 61000−4−2 (Contact)	V_{ESD}	±30 ±30	kV
Operating Temperature Range	T_J	−55 to +125	°C
Storage Temperature Range	Tstg	−55 to +150	°C

Electrical Characteristics (TA=25°C unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	V_{RWM}			3.3	V	
Breakdown Voltage	V_{BR}	4			V	I_T = 1mA
Reverse Leakage Current	I_R			0.07	uA	V_{RWM} = 3.3V
Clamping Voltage	V_C		7.5		V	Ipp=1A(8x 20us pulse)
Clamping Voltage	V_C			13	V	Ipp=8A(8x 20us pulse)
Junction Capacitance	C_J		13		pF	VR = 0V, f = 1MHz

Typical Performance Characteristics (T_A=25°C unless otherwise Specified)

Fig1. 8/20μs Pulse Waveform




Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)






Fig3. Power Derating Curve




SOD523 (0603) Package Outline Drawing



DIMENSIONS					
DIM	INCHES		MM [1]		NOTE
	MIN	MAX	MIN	MAX	
A	.043	.051	1.10	1.30	–
B	.028	.035	0.70	0.90	–
C	.059	.067	1.50	1.70	–
D	.020	.028	0.50	0.70	–
E	.010	.014	0.25	0.35	–
F	.004	.008	0.10	0.20	–
G	.020	.028	0.50	0.70	–

[1] CONTROLLING DIMENSION: MILLIMETERS

Suggested Land Pattern



DIMENSIONS					
DIM	INCHES		MM [1]		NOTE
	MIN	MAX	MIN	MAX	
C	–	.067	–	1.70	REF
G	–	.043	–	1.10	–
X	–	.031	–	0.80	REF
Y	–	.024	–	0.60	–
Z	–	.091	–	2.30	–

[1] CONTROLLING DIMENSION: MILLIMETERS

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TECH PUBLIC:

TPB05A40-323 TPESD5311N BV15C LTH7 BSN20W FDC6301N-TP TPB1A30-123 TPD1213A-02SM TPESD0402G08V DDTA143ZCA ESD5B5.0ST1G-P TPESD0504S6-A TPS7B6950DBVR-TP TPSPX3819M5-L-3-3 TPZXMP3A13FTA IRFR2405TRPBF-TP TPADM809SAKSZ SN7002W TPADM809LAKSZ TPFMMT493 TPS3809L30DBVR-TP TPWSB5557Z TPZVN3320FTA TPGC12C-1 DMP6350S FDMS7670AS-TP QM3003J-TP SI3932DV TPAPX809S-31SA TPDMG6602SVT