AQ1205-01LTG

7 pF, 7 A, SOD523, Bidirectional Discrete TVS Diode, General Purpose ESD Protection

AUTOMOTIVE GRADE HF RoHS Pb




Note: This package image is for example and reference only. for detail package drawing, please refer to the package section in this datasheet.

Pinout



Functional Block Diagram



Description

The AQ1205-01LTG bidirectional TVS is fabricated in a proprietary silicon avalanche technology. These diodes provide a high ESD (electrostatic discharge) protection level for electronic equipment. The AQ1205-01LTG TVS can safely absorb repetitive ESD strikes of ±30 kV (contact and air discharge as defined in IEC 61000-4-2) without any performance degradation. In addition, it can safely dissipate a 7 A 8/20 µs surge event as defined in IEC 61000-4-5, 2nd edition.

Features

- ESD, IEC 61000-4-2, ±30 kV contact/air
- ESD, ISO10605 330 pF 330 Ω, ±30 kV contact/air
- EFT, IEC 61000-4-4, 40 A (5/50 ns)
- Maximum surge tolerance, IEC 61000-4-5, 2nd edition, 7 A (8/20 µs)
- Low leakage current of 20 nA (Max) at 5 V
- Low clamping voltage
- Halogen-free, lead-free and RoHS compliant
- Moisture Sensitivity Level (MSL -1)
- AEC-Q101 qualified and PPAP capable

Applications

- Automotive
- Battery Protection
- BMS
- Computer Peripherals
- Medical Equipment
- Notebooks / Desktops / Servers
- Point-of-Sale Terminals
- Switches / Buttons
- Test Equipment / Instrumentation

PRELIMINARY

Life Support Note:

Not Intended for Use in Life Support or Life Saving Applications

The products shown herein are not designed for use in life sustaining or life saving applications unless otherwise expressly indicated.

© 2024 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: FW.11/07/24

AQ1205-01LTG

7 pF, 7 A, SOD523, Bidirectional Discrete TVS Diode, General Purpose ESD Protection

PRELIMINARY

Absolute Maximum Ratings

Symbol	Parameter	Value	Units
I_{PP}	Peak Current (t_p = 8/20 µs)	7	A
T_{OP}	Operating Temperature	-40 to 150	°C
T_{STOR}	Storage Temperature	-55 to 150	°C

Caution: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the component. This is a stress only rating and operation of the component at these or any other conditions above those indicated in the operational sections of this specification is not implied.


Electrical Characteristics (T_{OP} = 25 °C)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Units
Reverse Standoff Voltage	V_{RWM}				5	V
Breakdown Voltage	V_{BR}	I_R = 1 mA	5.1	5.5		V
Reverse Leakage Current	I_{LEAK}	V_R = 5 V			20	nA
Clamp Voltage[1]	V_C	I_{PP} = 1 A, t_p = 8/20 µs, I/O to GND		6.5		V
		I_{PP} = 7 A, t_p = 8/2 0µs, I/O to GND		10		V
Dynamic Resistance[2]	R_{DYN}	TLP, t_p = 100 ns, I/O to GND		0.16		Ω
ESD Withstand Voltage[1,3]	V_{ESD}	IEC 61000-4-2 (Contact Discharge)	±30			kV
		IEC 61000-4-2 (Air Discharge)	±30			kV
		ISO10605 (Contact Discharge)	±30			kV
		ISO10605 (Air Discharge)	±30			kV
Diode Capacitance[1]	C_{IO-GND}	Reverse Bias = 5 V, f = 1 MHz, I/O to GND		7	9	pF


Note:

1. Parameter is guaranteed by design and/or component characterization.
2. Transmission Line Pulse (TLP) with 100ns width, 0.2 ns rise time, and average window t1 = 70 ns to t2 = 90 ns
3. Device stressed with ten non-repetitive ESD pulses.

Capacitance vs. Reverse Bias



Clamping Voltage vs I_{PP}




© 2024 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: FW.11/07/24

AQ1205-01LTG


7 pF, 7 A, SOD523, Bidirectional Discrete TVS Diode, General Purpose ESD Protection

PRELIMINARY


Positive Transmission Line Pulsing (TLP) Plot




Negative Transmission Line Pulsing (TLP) Plot




IEC 61000-4-2 +8 kV Contact ESD Clamping Voltage




IEC 61000-4-2 -8 kV Contact ESD Clamping Voltage



ISO10605 Contact Discharge Plot at +8 kV



ISO10605 Contact Discharge Plot at -8 kV




© 2024 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: FW.11/07/24

AQ1205-01LTG

7 pF, 7 A, SOD523, Bidirectional Discrete TVS Diode, General Purpose ESD Protection


PRELIMINARY

8/20 µs Pulse Waveform



Soldering Parameters

Reflow Condition		Pb – free assembly
Pre Heat	- Temperature Min ($T_{s(min)}$)	150 °C
	- Temperature Max ($T_{s(max)}$)	200 °C
	- Time (min to max) (t_s)	60 – 120 secs
Average Ramp Up Rate (Liquidus) Temp (T_L) to Peak		3 °C/second max
$T_{S(max)}$ to T_L - Ramp-up Rate		3 °C/second max
Reflow	- Temperature (T_L) (Liquidus)	217 °C
	- Temperature (t_L)	60 – 150 seconds
Peak Temperature (T_P)		$260^{+0/-5}$ °C
Time Within 5 °C of Actual Peak Temperature (t_p)		30 seconds
Ramp-down Rate		6 °C/second max
Time 25 °C to Peak Temperature (T_P)		8 minutes max
Do Not Exceed		260 °C




Product Characteristics

Lead Plating	Matte tin
Lead Material	Copper alloy
Body Material	Molded compound
Flammability	UL recognized compound meeting flammability rating V-0


Ordering Information

Part Number	Package	Min. Order Qty.
AQ1205-01LTG	SOD523	5,000

Part Marking System



Part Numbering System




© 2024 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: FW.11/07/24

AQ1205-01LTG

7 pF, 7 A, SOD523, Bidirectional Discrete TVS Diode, General Purpose ESD Protection


PRELIMINARY

Package Dimensions — SOD523



Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	0.51	0.77	0.020	0.030
A1	0.50	0.70	0.020	0.028
b	0.25	0.35	0.010	0.014
c	0.08	0.15	0.003	0.006
D	0.70	0.90	0.028	0.035
E	1.10	1.30	0.043	0.051
E1	1.50	1.70	0.059	0.067
E2	0.20 REF		0.001 REF	
L	0.00	0.07	0.000	0.003
θ	7° REF		7° REF	

Embossed Carrier Tape & Reel Specification — SOD523



Symbol	Millimeters
A0	0.85min/1.01max
B0	1.91+/-0.08
W	8.0+0.3/-0.10
D0	1.50+0.10
D1	ø1.00min/ø1.25max
E1	1.75+/-0.10
F	3.50+/-0.05
P0	4.00+/-0.10
P	2.00+/-0.05
P1	2.00+/-0.05
K0	0.68min/0.78max
T	0.254+/-0.13

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at http://www.littelfuse.com/disclaimer-electronics.

Littelfuse®

© 2024 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: FW.11/07/24

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Littelfuse:

V150LA20AP 1812L150/24MR 2920L600/12MR SL1011A230A SM12-02HTG 03420828H 0481010.HXLP RF3304-000 0327020.LXS DNA30E2200PA P3100SBLRP RF1342-000 RF1543-000 0233006.MXP 0242.080UAT1 03540601ZXGY NANOSMDC200F-2 RF3305-000 TPSMD33CA MDSR-4-22-38 PAA140S 1.5SMC51CA 37014000430 60R250XF RF2562-000 8.0SMDJ16CA IXTP52P10P RF2682-000 1812L260/12MR TP5.0SMDJ43CA