Data Sheet

HUBER+SUHNER

Coaxial PCB Connector
82_MCX-S50-0-29/111_N

Description

Straight PCB jack

Interface Standards
IEC 60169-36_CECC 22220



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz

Mechanical Data

Board mounting type	surface mount
Weight	0.0004 kg

Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00012753
Catalogue drawing	DCA-00012755
Mounting hole	DOU-00012756

Ordering Information

Bulk 100 pcs package	82_MCX-S50-0-29/111_NH
Tape and Reel package	82_MCX-S50-0-29/111_NM
Single package	82_MCX-S50-0-29/111_NE

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Huber+Suhner:

PCRS_LCMX_LCMX_O421T_30.0_LL 11MMBXEF31616MMBX/300 12012090 1399.17.0210 84118385 RADOX 125 0.75 MMÂ² RED G032D/BNCm/BNCm/1000 16_MMCX-50-2-4/111_OH G032D/Nm/SMAm/1000 11_SMC-50-2-10/111_NE 12535682 22511964 23000457 23002145 6806.19.A 33_PC24-SK-50-2/199_NE 84093961 85201112 G_03130_HT-01 MINIBEND R-12 Minibend L-10 RG_196_A/U 11_TNC-50-3-116/133_NE 1399.17.0231 24_SMA-50-2-15/111_NH 6620_SMA-50-2/199_NE MINIBEND R-10 MINIBEND R-8 1399.31.0020 6601_PC185-50-1/199_NE