恒拓电子
HENGTUO ELECTRONICS

HENGTUO ELECTRONICS


HT series

Photo Coupler
Product Specification


HT-817X

恒拓电子
HENGTUO ELECTRONICS

■ Package



Schematic



Pin Configuration
1. Anode
2. Cathode
3. Emitter
4. Collector

■ Description

The HT-817X is a photoelectric coupler composed of light-emitting diode and phototransistor. It is packaged in a 4-pin package and in wide-lead spacing and SMD opition.

■ Features

- Current transfer ratio(CTR : MIN. 50% at IF = 5mA, VCE = 5V)
- High input-output isolation voltage(Viso = 5,000Vrms)
- Operating Temperature: -55℃~110℃
- Safety approval
  (UL 1577，VDE DIN EN60747-5-5（VDE 0884-5），CQC11-471543-2022)
- RoHS
- MSL1

■ Applications

- Programmable controllers
- Switching power supply, intelligent meter
- Home appliances: such as air conditioners, fans, water heaters, etc

HENGTUO ELECTRONICS

■ Product Nomenclature

The product name is designated as below:

HT -817 X -X X- X X X- XX
① ② ③ ④ ⑤ ⑥ ⑦

Designation:

HT =Hengtuo Technology Co.,LTD.
817= Product Series
① = Lead form option(S1,M,NONE)(1)
② = CTR Rank(A,B,C,D,E)(2)
③ = Tape and Reel option(TP,TP1,NONE)(3)
④ = Lead frame Material(F,NONE)(4)
⑤ = VDE order option(fixed code "V")
⑥ = Halogen free option(fixed code"G")
⑦ = Customer code

Notes

1. Lead form option:

Symbol	Description
S1	DIP4-S1
M	DIP4-M
NONE	DIP4 Normal

2. CTR Rank:

Symbol	Description
A,B,C,D,E...	CTR Rank
NONE	No Rank

3. Tape and Reel option:


Symbol	Description
TP&TP1	Tape and Reel Type
NONE	DIP Type

4. Lead frame Material

Symbol	Description
F	Iron
NONE	Copper

HENGTUO ELECTRONICS

■ Marking Information



Designation:

HT	denotes Hengtuo
817	denotes Device
C	denotes CTR Rank
YY	denotes year code
WW	denotes week code
V	denotes VDE

■ Maximum Ratings

	Parameter	Symbol	Values	Unit
Input	Forward Current	I_F	50	mA
	Reverse Voltage	V_R	6	V
	Power Dissipation	P	70	MW
	Peak Forward Current (100μs pulse, 100Hz)	I_{FP}	1	A
	Thermal Resistance Junction-Ambient	R_{thJ-A}	325	°C/W
	Thermal Resistance Junction-Case	R_{thJ-C}	200	°C/W
Output	Collector - Emitter Voltage	V_{CEO}	80	V
	Emitter - Collector Voltage	V_{ECO}	6	V
	Collector Current	I_C	50	mA
	Collector Power Dissipation	P_C	150	mW
Operating temperature range		T_{op}	–55 ~ 110	°C
Storage temperature range		T_{stg}	–55 ~ 125	°C
Total Power consumption		P(W)	200	mW
Isolation Voltage(1)		V_{ISO}	5000	Vrms
Soldering Temperature(2)		T_{SOL}	260	°C

Notes:
(1). AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1, 2 are shorted together, and pins 3, 4 are shorted together.
(2).For 10 seconds

■ Electronic Optical Characteristics

(TA = 25°C)

Parameter		Symbol	Min.	Typ.	Max.	Unit	Conditon
Input	Forward Voltage	V_F	-	1.2	1.4	V	I_F=20mA
	Reverse Current	I_R	-	-	10	μA	V_R=4V
	Terminal Capacitance	C_t	-	30	250	pF	V=0, f=1KHz
Output	Collector Dark Current	I_{CEO}	-	-	100	nA	VCE=20V, IF=0
	Collector-Emitter Breakdown Voltage	BV_{CEO}	80			V	IC=0.1mA, IF=0
	Emitter-Collector Breakdown Voltage	BV_{ECO}	6			V	IE=10μA, IF=0
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$		0.1	0.2	V	IF=20mA, IC=1mA
Isolation Resistance		R_{iso}	5×10^{10}	1×10^{11}	-	Ω	DC500V, 40 ~ 60% R.H.
Floating Capacitance		Cf		0.6	1	pF	V=0, f=1MHz
Cut-off Frequency		fc		80		kHz	VCE=5V, IC=2mA RL=100Ω,-3dB
Response Time (Rise)		tr		4	18	μs	VCE=2V, IC=2mA RL=100Ω,
Response Time (Fall)		tf		3	18	μs	

■ Rank Table Of Current Transfer Ratio

(CTR=IC/IF x 100%)

Rank Code	Symbol	Min	Max	Conditon
NONE	CTR	50	600	IF=5mA, VCE=5V, Ta=25°C
A		80	160	
B		130	260	
C		200	400	
D		300	600	

HENG TUO ELECTRONICS

恒拓电子
HENGTUO ELECTRONICS

■ Characteristics Curves

Fig.1 Allowable Forward Current VS Ambient Temperature




Fig.2 Allowable collector power disspation VSAmbient Temperature(℃)




Fig.3 Relative Current Transfer Ratio vs. Forward Current




Fig4 Forward Current vs. Forward Voltage




Fig.5 Collector Current vs. Collector-emitter Voltage




Fig.6 Relative Current Transfer Ratio vs.Ambient Temperature




Fig.7 Collector-emitter Saturation Voltage vs. Ambient Temperature




Fig.8 Collector Dark Current vs Ambient Temperature




Fig.9 Response Time vs. Load Resistance




Fig.10 Frequency Response




Fig.11 Collector-emitter Saturation Voltage vs Forward Current






Fig.12 Switching Time Test Circuit & Waveforms





恒拓电子
HENGTUO ELECTRONICS

■ Outline Dimension


DIP Normal Type:










DIP M Type:








SMD S1 Type:



Unit: mm
Tolerance: ±0.1mm

■ Recommended solder pad Design

For S1 type:



Unit: mm
Tolerance: ±0.1mm


恒拓电子
HENGTUO ELECTRONICS

■ Temperature Profile Of Soldering

1. IR Reflow soldering


(JEDEC-STD-020 compliant)

Profile item	Conditon
Preheat -Temperature Min (TSmin) -Temperature Max (TSmax) -Time (min to max) (ts)	 150°C 200°C 90±30 sec
Soldering zone -Temperature (TL) -Time (tL)	 217°C 60 sec
Peak Temperature (TP)	260°C
Ramp-up rate	3°C / sec max
Ramp-down rate	3~6°C/ sec



Notes:
One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.

2. Wave soldering (JEDEC22A111 compliant)




3. Hand soldering by soldering iron

Allow single lead soldering in every single process. One time soldering is recommended.
Temperature: 380+0/-5˚C
Time: 3 sec max.


■ Packing


1. Tape and Reel

Option TP:



Option TP1:





Deminsion/mm	W	E	F	P0	P1	P2
Packagetype:S	16±0.2	1.75±0.1	7.5±0.1	4±0.1	8±0.1	2±0.1

Deminsion/mm	A0	B0	D0	D1	K0	T
Packagetype:S	4.6±0.1	10.4±0.1	1.5±0.1	1.5±0.1	4.6±0.1	0.4±0.1

Packagetype:S	Reel	Inner carton	Outer carton
QTY/PCS	1.5K/reel	3K(2 reels)	30K

2. Tape and Tube

Packagetype:Normal&M	Tube	Outer carton
QTY/PCS	100	50K(50 tubes)

HENGTUO ELECTRONICS

■ Attention:

- Hengtuo is continually improving the quality, reliability, function or design and Hengtuo reserves the right to make changes without further notices.
- The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical application and instrumentation.
- For equipment/devices where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc, please contact our sales representatives.
- When requiring a device for any ”specific” application, please contact our sales in advice.
- If there are any questions about the contents of this publication, please contact us at your convenience.

HENG TUO ELECTRONICS

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HENGTUO:

HT817S1-BTP1-F HTM-3063-TP1 PC-3H7-CTP1(CW) HT-1018-TP1 HT-3H7-BTP1 HT-6N137-S1TA1 HT3053 PC-817S1-CTP1-F(CW) HT6-214 PC-1018-TP1(CW) PC-3H7-BTP1(CW) PC-817-C-F(CW) HT-1019-TP1 HT-3063-S1TA1 HT354-ATP1 HT354-BTP1 HT817-B-F HT-3053-S1TA1 HTM-3053-TP1 PC-357-CTP1(CW) HT-357-BTP1 HT3063 PC-1019-TP1(CW) HT-357-CTP1 HT817S1-CTP1-F PC-357-BTP1(CW) HT-3H7-CTP1 HT6N137 HT817-C-F