







General ordering data	
Order No.	1786280000
Part designation	TOP4GS11/180 6.35 OR
Version	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 11, 180°, Box
EAN	4032248200917
Qty.	50 pc(s).

System parameters	
Product family	System TOP4GS
Conductor connection system	TOP connection
Fitted to PCB	Soldered connection
Outgoing direction of conductor	180°
Pitch	6.35 mm
Pitch in inch	0.25 inch
No. of poles	11
Fitted by customer	no
No. of rows	1
Solder pin length	3.5 mm
Dia. of fitting hole	1.3 mm
Fitting hole tolerance	+ 0.1 mm
No. of solder pins per pole	2
Screwdriver blade	0.6 x 3.5
Screwdriver blade standard	DIN 5264
Tightening torque, min.	0.5 Nm
Tightening torque, max.	0.6 Nm
Clamping screw	M 3
Stripping length	13 mm
L1 in mm	63.5 mm
L1 in inch	2.5 inch

Material data	
Insulating material	PA
Colour	orange

Material data	
colour chart	Similar to RAL 2000
Insulating material group	I
Flammability class UL 94	V-2
CTI	>= 600
Contact base material	E-Cu
Contact surface	tinned
Storage temperature, min.	-25 °C
Storage temperature, max.	55 °C

Connectable conductors	
Clamping range, min.	0.13 mm²
Clamping range, max.	6 mm²
AWG, min.	26
AWG, max.	10
Solid, min. H05(07) V-U	0.5 mm²
Solid, max. H05(07) V-U	6 mm²
Flexible, min. H05(07) V-K	0.5 mm²
Flexible, max. H05(07) V-K	4 mm²
With wire end ferrule, acc. to DIN 46 228/1, min.	0.5 mm²
With wire end ferrule, acc. to DIN 46 228/1, max.	4 mm²
w. plastic collar ferrule, DIN 46228 pt 4, min.	0.5 mm²
w. plastic collar ferrule, DIN 46228 pt 4, max.	4 mm²
Gauge to EN 60999 a x b; ø	2.8 mm x 2.4 mm;

DIN IEC rating data	
Rated current, min. No. pins (Tu=20°C)	32 A
Rated current, min. No. pins(Tu=40°C)	32 A
Rated voltage for overvoltage class/pollution severity II/2	320 V
Rated voltage for overvoltage class/pollution severity III/2	320 V
Rated voltage for overvoltage class/pollution severity III/3	320 V
Rated impulse withstand voltage for overvoltage class/pollution severity II/2	2.5 kV
Rated impulse withstand voltage for overvoltage class/pollution severity III/2	2.5 kV
Rated impulse withstand voltage for overvoltage class/pollution severity III/3	2.5 kV

CSA rating data	
Rated voltage (Use group D)	300 V
Rated current (Use group D)	10 A
AWG conductor (field wiring), min.	26
AWG conductor (field wiring), max.	10

UL 1059 rating data	
Rated voltage (Use group D)	300 V
Rated current (Use group D)	10 A
AWG conductor, min.	26
AWG conductor, max.	10

UL 1059 rating data

Approvals

Approvals institutes



Downloads

CAD Library (P-CAD Format - Standard)	TOP 4GS.LIB

Classifications

ETIM 2.0	NK
ETIM 3.0	EC001284
eClass 4.1	NK
eClass 5.0	NK
eClass 5.1	NK

Similar products

Order No.	Part designation	Version
1786190000	TOP4GS2/180 6.35 OR	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 2, 180°, Box
1786200000	TOP4GS3/180 6.35 OR	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 3, 180°, Box
1786210000	TOP4GS4/180 6.35 OR	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 4, 180°, Box
1786220000	TOP4GS5/180 6.35 OR	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 5, 180°, Box
1786230000	TOP4GS6/180 6.35 OR	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 6, 180°, Box
1786240000	TOP4GS7/180 6.35 OR	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 7, 180°, Box
1786250000	TOP4GS8/180 6.35 OR	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 8, 180°, Box
1786260000	TOP4GS9/180 6.35 OR	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 9, 180°, Box
1786270000	TOP4GS10/180 6.35 OR	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 10, 180°, Box
1786290000	TOP4GS12/180 6.35 OR	PCB terminal, TOP connection, Soldered connection, Clamping range, max.: 6 mm², Pitch: 6.35 mm, No. of poles: 12, 180°, Box

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

WeidmÃ¼ller:

024892 SAKS3 1608570000 1784180000 1804580000 1607520000 1649300000 9456650000 1760040000
1779950000 1818090500 1121990000 1124150000 1289470000 2642470000 8690200000 9037380000
0303620000 1221360000 1906650000 8951460000 1013450000 1031470000 1622940000 1786450000
1950200000 1127570000 1608830000 1609820000 1890260000 2535780000